Pioneering for You



2022 – North America – 60 Hz.

#### **Product Guide**

Pumps and systems for HVAC, water supply, drainage and sewage.





Wilo USA Pumps and systems for building services, water management,	8
and groundwater applications.	
Scot Pump	30
Close-coupled cast iron, stainless steel, bronze and marine-specif pumps for OEM applications.	ic
Weil Pump	42
Heavy-duty pumps and systems for sump and sewage applications	5,
American-Marsh Pumps	52
End suction, process sump, non-clog, split-case, vertical multistage and vertical and submersible turbines.	je,

## DISCOVER WILO SOLUTIONS.

We offer a wide variety of intelligent pumps and systems to make our users' everyday lives simply more pleasant. Our energy-efficient solutions are suitable for residential, public, and commercial properties. Wilo products are used in heating, air conditioning, cooling, and water supply applications, as well as for drainage and sewage.

#### HEATING, AIR CONDITIONING, COOLING

Wilo delivers individual solutions and highly efficient technology for applications in heating, air conditioning, cooling, and domestic hot water.

#### WATER SUPPLY

Innovative products and systems from Wilo support applications in rainwater utilization, water supply and pressure boosting, fire fighting, and raw water intake.

#### DRAINAGE AND SEWAGE

Wilo pumps and lifting units ensure safe and reliable operation in drainage and sewage disposal.



## wilo<sup>®</sup>

Wilo

WILO USA LLC is a subsidiary of Wilo SE, headquartered in Dortmund, Germany. The Wilo Group is one of the world's leading premium suppliers of pumps and pump systems for building services, water management and the industrial sector. Wilo employs around 8000 people around the globe today. With innovative solutions, smart products and individual services, we provide the clever, efficient, and climate-friendly service of keeping water flowing. We already are the digital pioneer within the industry with our products and solutions, processes, and business models. In 2017 Wilo acquired Scot Pump, Weil Pump and component manufacturer Karak Machine Corporation. Wilo acquired Tennessee manufacturer American-Marsh Pumps in 2019.



#### **Get Boosted**

Ask us about our range of single to four-pump booster systems. With NSF/ANSI 61 certified pumps, touch screen interface, and high-efficiency pump options to handle all your boosting applications. Contact your Regional Sales Manager today for more information! That's what we call **Pioneering for You** 

#### +1 262-204-6600 | www.wilo-usa.com













elix SiBooster EXCEL

WiBooster

Helix Excel Complete

e Helix Complete

EFC Variable Speed Drive



Pioneering for You

#### **Building Services**

Pumps and systems for heating, air conditioning, cooling, pressure boosting, water supply, and sewage disposal in residential and commercial buildings.









#### Wilo-Stratos MAXO

Application

Max. Flow

280 GPM

Max. Head 52 feet

display

**Features & Benefits** 

→ EC Motor Technology

→ Maximum energy efficiency

→ Easy electrical installation

→ NEMA 2 Enclosure Protection

→ Green Button Technology with 4.3" LED color

functions, such as Dynamic Adapt plus, Multi-

 $\rightarrow$  Temp Range: 14 °F to 230 °F (-10°C to +110°C)

→ Electrical Connection: 1~115/230V, 1~230V

Flow Adaptation, T-const. and  $\Delta$ T-const.

→ Bluetooth for connection to mobile devices

 $\rightarrow$  New and innovative intelligent control

→ Hot Water Heating Systems

→ Industrial Circulation Systems

→ Air Conditioning Systems

→ Closed Cooling Circuits

**High-Efficiency Smart Circulators** 



#### H/ft Wilo-Stratos MAXO-D 60 Hz 50 40/ 40 30 20 30/ 80/

240

→ Green Button Technology with 4.3" LED color

functions, such as Dynamic Adapt plus, Multi-

 $\rightarrow$  Temp Range: 14 °F to 230 °F (-10°C to +110°C)

Flow Adaptation, T-const. and  $\Delta$ T-const.

→ Bluetooth for connection to mobile devices

→ New and innovative intelligent control

400 Q/US gpm

High-Efficiency Dual Smart Circulators

#### Application

Max. Flow

493 GPM

Max. Head

display

**Technical Data** 

**Features & Benefits** 

→ EC Motor Technology

→ Maximum energy efficiency

→ Easy electrical installation

→ Electrical Connection: 1~230V

→ NEMA 2 Enclosure Protection

52 feet

10

0

→ Hot Water Heating Systems

Wilo-Stratos MAXO-D

- → Air Conditioning Systems
- → Closed Cooling Circuits
- → Industrial Circulation Systems

#### Wilo-Stratos MAXO-Z

High-Efficiency DHW Smart Circulators



#### Application

- → Drinking Water
- → Domestic Hot Water Circulation Systems
- → Hot Water Heating Systems
- → Air Conditioning
- → Closed Cooling Circuits
- → Industrial Circulation Systems

#### Max. Flow

#### 240 GPM

Max. Head

#### 40 feet

#### Features & Benefits

- → EC Motor Technology
- → Green Button Technology with 4.3" LED color display
- $\rightarrow$  Highest standard of drinking water hygiene and energy efficiency
- → Thermal disinfection detection
- → Bluetooth for connection to mobile devices
- → Easy electrical installation

#### **Technical Data**

- → Certified to NSF/ANSI 61 & 372
- → Drinking Water Temp Range: 32°F to 176°F (0 °C to 80°C)
- → Heating Water Temp Range: 14°F to 230°F (-10 °C to 110°C)
- → Electrical Connection: 1~115/230V, 1~230V
- → NEMA 2 Enclosure Protection

#### **Materials of Construction**

- → ANSI 304 Stainless Steel construction
- $\rightarrow$  Carbon Bearing
- → Carbon Fiber Composite Impeller

- → Carbon Bearing
- → Carbon Fiber Composite Impeller

- → Gray Cast Iron with Cataphoretic coating

- → Carbon Fiber Composite Impeller

10

#### **Materials of Construction**

- → Gray Cast Iron with Cataphoretic coating

**Technical Data** 

- → Stainless Steel Shaft

- **Materials of Construction**
- → Stainless Steel Shaft
- → Carbon Bearing



11

**Building Services** 



#### Wilo-Stratos GIGA

High-Efficiency Inline Pumps



#### Application

- $\rightarrow$  Hot Water Heating Systems
- → Industrial Circulation
- → Closed Cooling Circuits
- $\rightarrow$  Air Conditioning Systems
- → Solar
- $\rightarrow$  Geothermal

#### Max. Flow

#### 550 GPM

Max. Head

167 feet

#### Features & Benefits

- $\rightarrow$  High efficient EC motor (IE5)
- → Single-stage, low pressure, in-line centrifugal pump
- → Highest-efficiency motor-drive combination on the market-up to 10HP with motor efficiencies up to 96%
- → Easy to operate 'Green Button' technology and LED display
- $\rightarrow\,$  Extremely compact and space–saving design
- $\rightarrow$  Integrated electronic power adjustment
- → Control range is up to three times as high as conventional electronically-controlled pumps
- → Integrated full motor protection
- → Multiple control modules available for integration with building management systems

#### **Technical Data**

- $\rightarrow$  High-corrosion protection due to cataphoretic coating
- $\rightarrow$  Power supply 380/480V~3, 50/60Hz, (±10%)
- → Temp Range:  $-4^{\circ}F(-20^{\circ}C)$  to  $248^{\circ}F(120^{\circ}C)$
- → Ambient Temp Range:  $32^{\circ}F(0^{\circ}C)$  to  $104^{\circ}F(40^{\circ}C)$
- → Max Operating Pressure: 232 PSI
- $\rightarrow$  IP55 enclosure, insulation class F
- $\rightarrow$  Control modes:  $\Delta$ PV,  $\Delta$ PC, constant speed, PID, Binary

#### **Materials of Construction**

- → Cast Iron, Cataphoresis Coated Volute
- → Cast Iron, Volute & Lantern
- → Engineered Composite Impeller
- → Stainless Steel Pump Shaft



#### Wilo-Helix EXCEL

High-Efficiency Multistage Pumps



#### Application

- → Water Supply and Pressure Boosting
- → Process Water
- → Pressure Washing Systems/Sprinkling Systems
- $\rightarrow$  Industrial Circulation Systems
- → Cooling Circuits & Condensate Return
- $\rightarrow$  Agriculture/Irrigation

#### Max. Flow

#### 395 GPM

#### Max. Head

807 feet

#### Features & Benefits

- → High efficient EC motor (IE5)
- → High-efficiency controller offers up to 70% speed reduction
- → Optimized 3D impellers for improved head and flow per stage
- → Cartridge mechanical seal for quick and easy maintenance
- → Variable pressure, constant pressure and variable speed control modes
- → Optional BACnet<sup>™</sup>, Modbus, LonWorks<sup>®</sup> interface modules

#### **Technical Data**

- $\rightarrow$  Voltage: 460V (+/- 10%), 60Hz
- → Fluid temp range: Models 10-80: -22 to 248°F (-30 to 120°C)
- Models 110–270: –4 to 248°F (–20 to 120°C)
- $\rightarrow$  Max operating pressure: 232/362 PSI
- $\rightarrow\,$  Class 300 ANSI Flanges standard on models  $\geq$  2"
- → Control modes:  $\Delta PV^{*1}$ ,  $\Delta PC^{*2}$ , constant speed,
- PID
- \*1 = Differential Transducer Kit available
   \*2 = Discharge Transducer available

#### Materials of Construction

→ Stainless Steel construction certified to NSF 61 (Models 10-80)



#### Wilo-Star S

3-Speed Wet Rotor Circulators



**Residential Wet Rotor Circulators** 



#### Application

- $\rightarrow$  Hot Water Heating Systems
- $\rightarrow$  Cold Water
- $\rightarrow$  Air Conditioning Systems
- $\rightarrow$  Water/Glycol concentrations up to 50%
- $\rightarrow$  Solar
- $\rightarrow$  Geothermal

#### Max. Flow

35 GPM

Max. Head

#### 33 feet

#### **Features & Benefits**

- → Reliable wet rotor technology
- $\rightarrow$  Quick connect wiring
- $\rightarrow$  Powerful starting torque
- $\rightarrow$  Ultra quiet
- ightarrow Installable hghi-temp check (RFC model)
- $\rightarrow$  RFC Patented Rotating Flange: US 8,297,664 B2

#### Technical Data

12

**Building Services** 

- → Max. temp range: 14°F to 230°F (-10°C to 110°C)
- $\rightarrow$  Max. Amb temp: 104°F (40°C)
- $\rightarrow$  Electrical Connection: 1~115v
- Star S33 available in 1~115v, 230v
- $\rightarrow$  Max. working pressure: 140 PSI (10 Bar)

#### **Materials of Construction**

- → Cast Iron Volute
- → Engineered Composite Impeller
- → Stainless Steel Shaft
- → Carbon Impregnated Bearing
- → Steel Terminal Box



#### Application

- $\rightarrow$  Hot Water Heating Systems
- → Cold Water
- → Air Conditioning Systems
- → Water/Glycol concentrations up to 50%
- → Solar
- $\rightarrow$  Geothermal

#### Max. Flow

#### 38 GPM

Max. Head

#### 33 feet Features & Benefits

- → Reliable wet rotor technology
- $\rightarrow$  Quick connect wiring
- $\rightarrow$  Powerful starting torque
- → Ultra quiet

#### **Technical Data**

- → Max. temp range: 14°F to 230°F (-10°C to 110°C)
- $\rightarrow$  Max. Amb temp: 104°F (40°C)
- → Electrical Connection: 1~115v
- $\rightarrow$  Max. working pressure: 140 PSI (10 Bar)

#### **Materials of Construction**

- $\rightarrow$  Cast Iron Volute
- → Engineered Composite Impeller
- → Stainless Steel Shaft
- → Carbon Impregnated Bearing
- → Steel Terminal Box

#### Wilo-Top S

**Commercial Wet Rotor Circulators** 



#### Application

- → All types of Hot Water Systems
- $\rightarrow$  Closed Cooling Circuits
- $\rightarrow$  Air Conditioning Systems
- → Industrial Circulation
- $\rightarrow$  Water/Glycol concentrations up to 50%
- → Solar → Geothermal

#### Max. Flow

#### 290 GPM

Max. Head

#### 70 feet

#### **Features & Benefits**

- → No mechanical seal
- $\rightarrow$  Quiet, low maintenance wet rotor circulator
- $\rightarrow$  Two-speed operation on all voltages
- → Automatically vented
- $\rightarrow$  Cataphoretically coating prevents corrosion
- $\rightarrow$  Sturdy cast aluminum electrical box
- $\rightarrow\,$  Short flange to flange dimension

#### **Technical Data**

- → Max temp range: 14°F to 248°F (-10°C to 120°C)
- → Amb Temp range:  $32^{\circ}F-104^{\circ}F$  ( $0^{\circ}C 40^{\circ}C$ )
- → Electrical Connection: 1~115v, 230v 3~208-230v, 460v, 575v
- $\rightarrow$  Max. working pressure: 145 PSI (10 Bar)

#### **Materials of Construction**

- $\rightarrow$  Cast Iron, Cataphoretically Coated Volute
- $\rightarrow$  Engineered Composite Impeller
- $\rightarrow$  Stainless Steel Shaft
- $\rightarrow$  Impregnated Carbon Bearing
- → Class H Insulation







#### Wilo-Star Z

Stainless Steel 3–Speed Wet Rotor Circulators





**Domestic Hot Water Circulators** 

#### Application

- $\rightarrow$  Potable Water Systems
- $\rightarrow$  Air Conditioning Systems
- → Open Systems-Heating or Cooling
- → Industrial Circulation
- $\rightarrow$  Water/Glycol concentrations up to 50%
- $\rightarrow$  Solar

 $\rightarrow$  Geothermal

#### Max. Flow

35 GPM

Max. Head

33 feet

#### **Features & Benefits**

- → Reliable wet rotor technology
- $\rightarrow$  Quick connect wiring
- $\rightarrow$  Powerful starting torque
- $\rightarrow$  Ultra quiet

#### **Technical Data**

- → Max. temp range: 14°F to 230°F (-10°C to 110°C)
- $\rightarrow$  Max Amb temp: 104°F (40°C)
- $\rightarrow$  Electrical Connections: 1~115v
- → Max. working pressure: 140 PSI (10 Bar)

#### **Materials of Construction**

- → Stainless Steel Volute & Shaft
- → Engineered Composite Impeller
- → Impregnated Carbon Bearing

#### Application

Wilo-Z 15+

→ Domestic Hot Water Recirculation

#### Max. Flow

#### 5.5 GPM

#### Max. Head

#### 9 feet

#### **Features & Benefits**

- → Compact design
- $\rightarrow\,$  Conserves energy and water
- $\rightarrow$  CSA compliant to NSF-61
- $\rightarrow$  Optional digital timer
- → Quick installation
- $\rightarrow$  115V power cord included

#### **Technical Data**

- → Water temp range: 32°F to 160°F (0°C to 71°C)
- → Max. working pressure: 145 PSI (10 Bar)
- → Electrical Connections: 1~115v, 60Hz
- → Protection Class: NEMA 12

#### **Materials of Construction**

- → Impeller: Composite/40% Glass filled (PA66G40)
- → Shaft: Ceramics
- $\rightarrow$  Rotor core: Silicon steel sheet + copper strip





Wilo-Z 15+ Accessories

JetValve, Digital Timer & DHW Fitting Pack



Wilo Accessories Flanges & Ball Valves

#### Application

- $\rightarrow\,$  Mounts under the sink for instant hot water
- $\rightarrow$  Adjustable temperature setpoint screw
- $\rightarrow$  1/2" Hot and cold male IPS inlets
- $\rightarrow \, 3/8"$  Hot and cold male compression thread outlets
- → Available as standalone valve or with 20" Stainless Steel flex connectors
- → Conserves water

#### **Digital Timer**

- → Weekly digital timer
- → Large LCD display
- → Conserves energy

#### **DHW Fitting Pack**

- → Package of four (4) connectors to handle all types of piping
- → Two (2) ½" SW x FNPT
- $\rightarrow$  Two (2) <sup>3</sup>/<sub>4</sub>" SW x FNPT
- $\rightarrow$  Two (2) 3/4" SW x 1/2" SW Reducing Bushings
- $\rightarrow$  Two (2) <sup>3</sup>/<sub>4</sub>" Street Hub Copper Unions
- $\rightarrow$  Less than 0.25% Lead content

#### Application

- → Residential FNPT cast iron flanges (¾", 1", 1¼", 1½")
- $\rightarrow$  HV cast iron FNPT flanges
- (1", 1½", 2")
- $\rightarrow$  Wilo cast iron FNPT "Check Flange" kit
- (¾", 1", 1¼")

#### **Bronze Flanges**

- $\rightarrow$  Lead-free bronze
- → Residential FNPT bronze flanges (¾", 1", 1¼")
- → Residential SWT bronze flanges (¾", 1")
- → HV bronze flanges (Top S, Stratos, Star 17) (1", 1¼, 2")

#### Swivel Flange Ball Valves

- → Residential FNPT/SWT w check
- (¾", 1", 1¼", 1½") → HV FNPT/SWT
- (1¼", 1½")





Submersible Sump Pumps

wilo

#### Wilo-ECC

Submersible Sump Pumps



#### Application

- → Sump & Effluent
- → Dewatering
- $\rightarrow$  Drainage

#### 

#### Application

Wilo-ECS

- → Sump & Effluent
- $\rightarrow$  Dewatering
- $\rightarrow$  Drainage

#### Wilo-WCC

Sewage/Effluent Pumps



#### Application

- → Residential Sewage & Effluent
- $\rightarrow$  Drainage

Max. Flow	
58 GPM	

#### Max. Head

25 feet

#### Features & Benefits

- → Permanent split capacitor motor with automatic thermal overload protection
- $\rightarrow$  10' power cord included

#### Max. Flow

#### 71 GPM

#### Max. Head

#### 23 feet

#### Features & Benefits

- $\rightarrow$  Oil-filled motor for max heat dissipation
- $\rightarrow$  Ideal for basement installations  $\rightarrow$  10' power cord included

#### Max. Flow

85 GPM

#### Max. Head

24 feet

#### Features & Benefits

- $\rightarrow$  Replaceable piggyback tether float switch
- $\rightarrow$  Oil-filled motor for maximum heat dissipation
- $\rightarrow\,$  Built–in thermal overload protection
- $\rightarrow$  10' power cord included

#### **Technical Data**

- → Max. Solids size: 3/8"
- $\rightarrow$  Max. fluid temp: 77°F (25°C)
- $\rightarrow$  Electrical Connections: 1~115v
- $\rightarrow$  1½" NPT Discharge (1¼" with adapter)

#### **Materials of Construction**

- $\rightarrow$  Cast Iron Volute & Motor Housing
- $\rightarrow$  Engineered Composite Impeller
- $\rightarrow$  Stainless Steel Bottom-Screened Inlet

#### Technical Data

- → Max. Solids size:  $\frac{1}{2}$ "
- $\rightarrow$  Max. fluid temp: 77°F (25°C)
- → Electrical Connections: 1~115v
- $\rightarrow$  1½" Discharge (1¼" adapter included)

#### **Materials of Construction**

- $\rightarrow$  Cast Iron Volute
- $\rightarrow\,$  Stainless Steel Motor Housing
- $\rightarrow$  Engineered Composite Impeller

#### **Technical Data**

- → Max. Solids size: 2" (WCC17); ¾" (WCC28)
- $\rightarrow$  Max. fluid temp: 130°F (55°C)
- → Electrical Connections: 1~115v
- → 2" NPT Discharge

#### **Materials of Construction**

- → Cast Iron Volute & Motor Housing
- → Engineered Composite Impeller

#### 15

## **Building Services**

Packaged Booster System & Multistage Pumps



#### Wilo-Helix V

High-Pressure Vertical Multistage Centrifugal Pumps



#### Application

- $\rightarrow$  Water Supply
- → Pressure Boosting
- → Condensate Return
- $\rightarrow$  Boiler Feed
- → Washing/Sprinkling
- → Process Engineering
- $\rightarrow$  Cooling Circuits

#### Max. Flow

380 GPM

#### Max. Head

800 feet

#### **Features & Benefits**

- $\rightarrow$  Cartridge seal design for easy serviceability
- → 3D Laser welded Impellers for improved hydraulic efficiency
- → Integrated thrust bearings for reduced motor stress
- → Pump lifting lugs
- $\rightarrow$  Heavy-duty pump base

#### Technical Data

- → NEMA Premium Efficiency Motors
- → Fluid temp range: -4°F to 248°F (-20°C to 120°C)
- → Electrical Connections: 3~208-230/460/575V
- → Flange Connection: Class 300 ANSI on models ≥ 2"
- $\rightarrow$  Pressure range: 232 PSI or 363 PSI

#### **Materials of Construction**

- → 304 Stainless Steel construction
- $\rightarrow$  Certified to NSF/ANSI 61
- $\rightarrow\,$  Stainless Steel Volute, Impeller & Shaft
- → Mechanical Seal options: Tungsten Carbide/ EPDM, or optional Viton<sup>®</sup>/FKM



#### Wilo-Helix EXCEL Complete

High-Efficiency, ECM Driven, Single-Pump Boosting Systems



#### Application

- → Water Supply
- → Pressure Boosting
- $\rightarrow$  Cooling Systems
- → Boiler Feed
- → Pressure Washing
- → Irrigation
  Max. Flow

#### 395 GPM

- Max. Head
- 807 feet

#### Features & Benefits

- → High efficient EC motor (IE5)
- → High-efficiency controller offers up to 70% speed reduction
- → Optimized 3D impellers for improved head and flow per stage
- → Cartridge mechanical seal for quick and easy maintenance
- $\rightarrow\,$  Variable pressure, constant pressure, and variable speed control modes
- → Optional BACnet<sup>™</sup>, Modbus, LonWorks<sup>®</sup> interface modules

#### **Technical Data**

- → Voltage: 460V (+/- 10%), 60Hz
- → Fluid temp range: Models 10-80: -22°F to 248°F (-30°C to 120°C)
- → Models 110-270: -4°F to 248°F (-20°C to 120°C)
- → Max operating pressure: 232/362 PSI
- → Flange Connection: Class 300 ANSI on models ≥ 2"

#### **Materials of Construction**

 $\rightarrow$  Stainless Steel construction certified to NSF 61 (Models 10-80)

#### Wilo-SiBooster EXCEL

High-Efficiency, ECM Driven Pressure-Boosting Systems



#### Application

- → Water Supply
- → Pressure Boosting
- $\rightarrow$  Agriculture
- → Washing/Sprinkling Systems
- → Cooling Circuits
- → Condensate Return

#### Max. Flow

1,578 GPM

#### Max. Head

807 feet

#### Features & Benefits

- $\rightarrow$  High efficient EC motor (IE5)
- $\rightarrow$  Real-time diagnostics and remote monitoring
- → Full system kWh energy reporting
- → Easy to use 7" touchscreen interface
- → Onboard Modbus and optional BACnet<sup>™</sup>, LonWorks<sup>®</sup> interface modules
- → Variable speed control per pump
- → Adjustable low pressure cut-out
- → Balanced run time for all pumps

#### **Technical Data**

- → Fluid temp range: -22°F to 248°F (-30°C to 120°C)
- → Electrical Connections: 3~460V
- → Rated pressure: 232 or 363 PSI depending on number of pump stages
- → System Connection: 150 or 300 Class ANSI flanges depending on maximum system pressure
- $\rightarrow$  TEFC motors standard

#### **Materials of Construction**

- → All 304 Stainless Steel construction
- $\rightarrow$  Entire packaged systems are listed under UL for NSF/ANSI 61
- → Entire packaged systems are listed under UL for QCZJ "packaged pumping systems".
- → EPDM/FKM Elastomers
  - → Mechanical Seal options: Tungsten Carbide/EPDM, or optional Viton<sup>®</sup>/FKM





#### **Wilo-Helix Complete**

1 Pump Pressure Boosting-Systems



2-4 Pump Pressure-Boosting Systems

#### Wilo-WiBooster



#### Application

- → Water Supply
- → Pressure Boosting
- → Condensate Return
- → Boiler Feed
- → Washing/Sprinkling
- → Process Engineering
- → Cooling Circuits

#### Max. Flow

#### 400 GPM

Max. Head

#### 780 feet

#### **Features & Benefits**

- → NSF 61 and 372 rated for water quality
- $\rightarrow$  UL QCZJ rated as a complete pumping package
- → Optimizes energy consumption based on system
- requirements
- $\rightarrow$  End of curve detection
- $\rightarrow$  Dry run prevention
- $\rightarrow$  Low flow protection
- $\rightarrow$  Pipe fill mode
- → Warnings & alarm indication

#### **Technical Data**

- → Fluid temp range: -4°F to 248°F (-20°C to 120°C) with a minimum of 32°F for domestic water
- → Electrical Connections: 3~208/230/460/575V
- → Rated pressure: 232/363 PSI
- → Flange Connection: Class 300 ANSI on models  $\geq 2$ "

#### **Materials of Construction**

- → Stainless Steel AISI 304 pump volute, flanges, impeller, stage housing and diffusers
- → Stainless Steel AISI 304 or AISI 318LN shaft
- → Stainless Steel AISI 316L shaft sleeve



#### Application

- → Water Supply
- → Pressure Boosting
- → Agriculture
- → Washing/Sprinkling Systems
- → Cooling Circuits
- → Condensate Return

#### Max. Flow

1,600 GPM

#### Max. Head

#### 580 feet

#### **Features & Benefits**

- → Real-time diagnostics and remote monitoring
- → Full system kWh energy reporting
- → Easy to use 7" touchscreen interface
- $\rightarrow$  Onboard Modbus and optional BACnet<sup>m</sup>, LonWorks<sup>®</sup> interface modules
- → Variable speed control per pump
- → Adjustable low pressure cut-out
- → Balanced run time for all pumps

#### **Technical Data**

- $\rightarrow$  Fluid temp range: -4°F to 248°F (-20°C to 120°C) with a minimum of 32°F for domestic water
- → Electrical Connections: 3~208-
- 230/460/575V → Rated pressure: 232/363 PSI
- → Flange Connection: 150 Class ANSI
- → TEFC motors standard

#### **Materials of Construction**

- → All 304 Stainless Steel construction
- → Entire packaged systems are listed under UL for NSF 61 and NSF 372
- → Entire packaged systems are listed under UL for QCZJ "packaged pumping systems"
- → EPDM/FKM Elastomers
- → Mechanical Seal options: Tungsten Carbide/EPDM, or optional Viton®/FKM

2-4 Pressure Boosting-Systems



#### Application

- → Water Supply
- → Pressure Boosting
- $\rightarrow$  Agriculture
- → Washing/Sprinkling Systems
- $\rightarrow$  Cooling Circuits
- → Condensate Return

#### Max. Flow

1,600 GPM

#### Max. Head

275 feet

#### **Features & Benefits**

- → Includes Scot 320–328 series Stainless Steel pumps
- → Real-time diagnostics and remote monitoring
- → Full system kWh energy reporting
- → Easy to use 7" touchscreen interface
- → Onboard Modbus and optional BACnet<sup>™</sup>, LonWorks® interface modules
- → Adjustable low pressure cut-out
- → Balanced run time for all pumps

#### **Technical Data**

 $\rightarrow$  Fluid temp range: -4°F to 140°F (-20°C to 60°C) with a minimum of 32°F for domestic water

→ 4-20 mA, ¼" Stainless Steel Pressure Transducers

 $\rightarrow$  All wetted components are of 304 Stainless Steel

→ Entire packaged systems are listed under UL for

→ Entire packaged systems are listed under UL for

QCZJ "packaged pumping systems"

17

**Building Services** 

→ Premium efficient NEMA motors  $\rightarrow$  VFD-Controlled system operation

→ Flange Connection: 150 Class ANSI

→ Rated pressure: 150 PSI

**Materials of Construction** 

NSF 61 and NSF 372

→ EPDM/FKM Elastomers

→ Type 21 Mechanical Seal

construction





#### Wilo-IL

In-line Centrifugal Pumps



#### Application

- → Hot Water Heating systems
- → Closed Cooling Circuits
- → Air Conditioning
- $\rightarrow$  Industrial Circulation
- $\rightarrow$  Solar
- $\rightarrow$  Geothermal

#### Max. Flow

1,450 GPM

Max. Head

440 feet

#### Features & Benefits

- $\rightarrow$  Integral suction diffuser cast in volute inlet
- → All bolts "non-metric"
- $\rightarrow$  Pump feet drilled and tapped
- $\rightarrow$  Class 125 ANSI standard flanges

#### **Technical Data**

- → TEFC motors standard (ODP available)
- → Fluid temp range: -4°F to 248°F (-20°C to 120°C)
- $\rightarrow$  Max. Amb temp: 104°F (40 °C)
- → Electrical Connections: 1~115v, 230v3~208-230v, 460v, 575v

#### **Materials of Construction**

- → Cast Iron EN-GJL-250 pump volute
- → Trimmable Bronze Impeller
- → Stainless Steel Stub Shaft

#### Wilo-IPL

In-line Pumps



#### Application

- → Hot Water Heating systems
- $\rightarrow$  Closed Cooling Circuits
- → Air Conditioning
- → Industrial Circulation
- $\rightarrow$  Solar
- $\rightarrow$  Geothermal

#### Max. Flow

- 400 GPM
- Max. Head

#### 65 feet

Features & Benefits

- $\rightarrow\,$  Integrated suction straightening vane
- $\rightarrow$  Pump feet drilled and tapped
- $\rightarrow$  Class 125 ANSI standard flanges
- $\rightarrow\,$  Suction and discharge pressure gauge tappings
- $\rightarrow$  Lifting eyes for easy installation

#### Technical Data

- $\rightarrow$  TEFC motors standard (ODP available)
- → Fluid temp range: 15°F to 250°F (-10°C to 120°C)
- $\rightarrow$  Max. Amb temp: 104°F (40 °C)
- → Electrical Connection: 1~115v, 230v 3~208-230v, 460v, 575v

#### **Materials of Construction**

- → Cast Iron, Cataphoretically Coated Volute
- → Engineered Composite Impeller
- → Stainless Steel Stub Shaft
- $\rightarrow$  2-Part Epoxy paint







#### Wilo-NL-HE

**Base Mounted End Suction Pumps** 



#### Application

- → Heating and Cooling systems
- → Air Conditioning
- → Municipal Water Supply
- $\rightarrow$  Pressure Boosting
- → Raw Water Intake
- → Irrigation/Agriculture
- → Industrial Process

#### Max. Flow

3,000 GPM

#### Max. Head

475 feet

#### **Features & Benefits**

- → Stainless Steel impeller
- $\rightarrow$  High-efficiency
- → Improved Hydraulic design
- → Energy Savings
- $\rightarrow$  Cataphoretic coating of all cast iron components
- → High corrosion resistance
- $\rightarrow$  Long service life
- → Easy maintenance
- $\rightarrow$  C-channel construction welded base

#### **Technical Data**

- → Fluid temp range: -4 °F to 284 °F
- $\rightarrow$  ANSI Class 125
- $\rightarrow$  Maximum operating pressure of 232 PSI
- → Main Connection 3~[208-230/460V, 575V] 60Hz
- → EN 1.4408 (Equivalent: AISI 316) Stainless Steel Impellers
- → DIN 1.4021 (Equivalent: 420) Stainless Steel Pump Shaft
- → Antimony Impregnated Carbon/Silicon Carbide/ EPDM(E1) Stainless Steel Spring & Body mechanical seal
- $\rightarrow$  NEMA Premium Efficient Motors

#### Materials of Construction

- ightarrow Stainless Steel Impeller and pump shaft
- → Carbon/silicon carbide/ EPDM (E1) mechanical

seal

#### Wilo-SCP

Split Case Pumps



#### Application

- → Heating and Cooling systems
- → Transfer and Pressure Boosting
- $\rightarrow$  Boiler Feed/Condensate
- → Municipal Water Supply
- $\rightarrow$  Irrigation
- $\rightarrow$  Industrial Applications

#### Max. Flow

#### 5,000 GPM

#### Max. Head

180 feet

#### **Features & Benefits**

- → Horizontal split casing allows replacement of bearings and mechanical seal without disturbing the system piping
- → Double suction design available for maximum efficiencies
- → Hydraulically balanced double-suction impeller for minimal axial thrust
- → Tongue and groove neck ring design
- eliminates seizing of rotating assembly → Pump shaft guards

#### **Technical Data**

- → Fluid temp range: 18°F to 250°F (-8°C to 120°C)
- → Available in sizes up to 500HP

#### **Materials of Construction**

- $\rightarrow$  9 different material specs available
- $\rightarrow$  8 different seal types available
- → Standard Configuration: Cast Iron Volute, Bronze Impeller, Stainless Steel Shaft, C/ SiC/EPDM Mechanical Seal, NEMA Standard Motors

#### Water Management

Pumps and pump systems for water supply, sewage collection, and wastewater treatment.

14

A REAL

a sur



## Our goal is to profitably grow the Parts & Service business by expanding our offerings, enlarging our customer base, and offering best-in-class quality and delivery.

- → The Aftermarket team is designed to support customers in all aspects post-shipment of new products. We have people dedicated to replacement parts sales, warranty support, field support, and pump repairs.
- → Field capabilities for all Wilo USA brands (Wilo, American–Marsh Pumps, Scot Pump, and Weil Pump) are:
  - Start-up services for new installations
  - End-user training on our equipment
  - · Provide regular and predictive maintenance to the installed equipment
  - Service agreements
  - Troubleshoot existing installations if necessary
- $\rightarrow$  In addition to the field capabilities, we have tools and equipment to provide field solutions to our end users.
  - Wilo Care A monitor installed equipment remotely.
  - Wilo Live Assistant A tool to remotely troubleshoot before arriving on site.
  - Connect Tool Standalone tool that tracks potential disturbances on-site (pressure, vibration, temperature, etc). We connect to the end-user product and monitor via the cloud.
  - Field Equipment Flowmeters, vibration equipment, alignment equipment, 3D scanner, etc.
- → Inhouse capabilities include:
  - Pump repairs, rehabs, and modifications to any existing pumping equipment.
  - Wilo's technical abilities involve disassembly, inspection, repair, and rebuild to extend the equipment's life.
- → Authorized Service Centers (ASCs) are designed to be an extension of Wilo and offer repair services for the installed equipment. We are in the process of evaluating and adding additional ASCs to support the American–Marsh product lines.

#### For more details contact:

Steve Wilson Aftermarket Sales Manager steve.wilson@wilo.com M +1 (816) 845-0411 Submersible Sewage Pumps



#### Wilo-Rexa CUT

Submersible Sewage Pumps with Macerator



#### Application

- → Domestic sewage
- → Municipal pressure sewer
- → Residential pressure sewer

#### Max. Flow

80 GPM

Max. Head

140 feet

#### Features & Benefits

- → High operational reliability through sphericallyformed macerator with pulling cut
- → Cutter design yields fine solids for non-clogging operation
- → Resistant to obstructions and blockages
- → Sealing chamber
- → Long service life through a high-quality motor seal with two independent mechanical seals and optional pencil electrode for sealing chamber control
- → cCSAus approval

#### **Technical Data**

22

Water Management

- → Power connection: 1~230 V/60 Hz, 3~230 V/60 Hz or 3~460 V/60 Hz
- → Submerged operating mode: continuous duty (S1)
- → Non-submerged operating mode: rated minutes operation (S2-15 or S3 10%)
- $\rightarrow$  Submerged under pressure (IP 68) → Insulation class: F
- $\rightarrow$  Max. fluid temp: 37 °F-104 °F (3°C-40 °C)

#### **Materials of Construction**

- → Cast Iron Volute
- → Cast Iron Impeller
- → Stainless Steel Motor Housing
- → Seals: SiC/SiC (pump side), C/MgSiO4 (Motor)
- → Macerator: Stainless Steel AISI 440B+Co

#### Wilo-FA

Submersible Sewage Pumps



#### Application

- → Sewage Collection
- → Storm Water
- → Raw Water
- → Sewage Treatment
- → Dewatering
- → Industry

#### Max. Flow

40,000 GPM

#### Max, Head

420 feet

#### **Features & Benefits**

- → Rugged design for portable, wet pit, and dry well installation
- $\rightarrow$  Shaft-Short overhang/large diameter
- $\rightarrow$  L3/D4 Shaft Bending ratio lowest in industry → Continuous operation possible in Q vs H
- curve extremes
- → Internally closed-loop cooled motors available
- → FM explosion-proof rated

#### **Technical Data**

- → S1 Operating Mode (continuous duty)
- → Protection class: IP 68
- $\rightarrow$  Max. temp: 104°F (40°C) (higher temperatures on request)
- → Silicon carbide mechanical seals

#### **Materials of Construction**

- → Cast Iron Volute (standard)
- → Stainless Steel Standard Shaft
- → For corrosive fluids, the external surfaces can be coated with Wilo-Ceram C0
- → Optional materials of construction and coatings available



#### Wilo-Rexa PRO

Submersible Sewage Pumps



#### Application

- $\rightarrow$  Wastewater and sewage
- → Domestic and site drainage

#### Max. Flow

550 GPM

#### Max. Head

110 feet

#### Features & Benefits

- → Clog-resistant vortex and 1-vane
- $\rightarrow$  FM explosion-proof rated
- → Dual mechanical shaft seals
- → Watertight cable inlet
- → Quick and easy installation

#### **Technical Data**

- → Electrical Connections: 1~ 230v, 3~ 230v, 460v
- → Protection class: IP 68, Insulation class: F
- $\rightarrow$  Max. fluid temp: 37°F-104°F (3°C-40°C)
- → Wet pit only
- $\rightarrow$  Solids passage up to 3 in
- $\rightarrow$  Max. immersion depth: 66 ft (20m)

#### Materials of Construction

- → Cast Iron Volute, Impeller and Motor Housing
- → Seals: SiC/SiC (pump side), C/MgSiO4 (Motor)

- - - - → Sludges up to 8% dry matter
      - → Municipal and industrial applications







#### **Wilo-FA Options**

#### Solid Impeller, Block Seal, Materials, Designs

#### Solid Impeller

- → Applications: high solids content (rags and fibrous), untreated sewage, local drainage
- → Smooth operation in wet and dry well installation
- → Simple installation via suspension unit or pump base
- $\rightarrow$  Impeller trimmed to specific duty point
- → Free passage: 3x4-7x7 in (78x105 -170x170 mm).

#### **Enclosed Block Seal**

Mechanical shaft seals of high-wear resistant silicon-carbide at the motor and pump-side integrated in a Stainless Steel cartridge

- → Short-height compact design (short-shaft overhang)
- → High operation safety
- → Durable and long life
- $\rightarrow$  Operation independent of the direction of rotation

#### **Special Materials**

- → Wear-resistant materials and coatings
- → Corrosion-resistant materials and coatings
- → Ceram coatings

#### **Special Designs**

- → Mechanical mixing head
- → Cast Stainless Steel
- → High chrome cast iron



#### Application

- → Low head water/sewage delivery at high flow rates
- $\rightarrow$  Process, raw, pure, and cooling water
- $\rightarrow$  Generation of fluid current in water channels

#### Max. Flow

30,000 GPM

#### Max. Head

#### 17 feet

#### **Features & Benefits**

- → Submersible, compact installation unit
- $\rightarrow$  In-line design
- → Energy efficient, flow-optimized, self-cleaning propellers, partially with helix hub
- $\rightarrow$  Low cost in–basin piping
- $\rightarrow$  FM–Ex Rated
- $\rightarrow\,$  Pump station wet wells are no longer necessary
- $\rightarrow$  Easy installation and removal
- → The special blade design provides gentle pumping of water, sewage, and activated sludge

#### **Technical Data**

- → Submerged operating mode: S1 (continuous duty)
- $\rightarrow$  Max temp: 104°F (40°C)
- $\rightarrow$  Protection class: IP 68
- $\rightarrow$  Units are planetary gear or direct driven

#### **Materials of Construction**

 $\rightarrow$  PUR or Stainless Steel Propeller

#### Wilo-Zetos K8, K10

Heavy-duty Cast Stainless Steel Submersible Pumps

BEST IN CLASS EFFICIENCIES!



#### Application

- → Drinking Water Supply
- → Clean Water Treatment
- $\rightarrow$  Water Supply
- $\rightarrow$  Pressure Boosting
- $\rightarrow$  Irrigation
- → Agriculture
   → Industrial Process

#### Max. Flow

#### 2,070 GPM

#### Max. Head

2.100 feet

#### **Features & Benefits**

- → NSF/ANSI 61 & 372 Certified
- → M6-M8-M9-M12 Motor options
- $\rightarrow$  ZK8 up to 84% hydraulic efficiency
- $\rightarrow$  ZK10 up to 88% hydraulic efficiency
- → Optional Ceram<sup>®</sup> coating (call for options)
- → Ceram<sup>®</sup> CT for higher efficiency and longer life on drinking water applications
- → Ceram<sup>®</sup> CP High–Temp Teflon coating for industrial applications

#### **Technical Data**

- → Electrical Connection: 3~200V-2300V
- → Liquid temp range: 32°F to 122°F (0°C to 50°C)
- → Max Sand Content: 150 ppm
- → Max Immersion Depth: 1000'
- → Protection Class: IP 68

#### **Materials of Construction**

- → Stainless steel housing parts and impellers (EN 1.4408)
- → K8: Threaded connection with non-return valve
  - K10: Threaded connection or flange connection, each with non-return valve

#### Wilo-RZP Recirulation Pumps

#### Submersible Mixers



#### Wilo-Flumen OPTI, EXCEL

#### High-Speed Submersible Mixers

#### Application

- → Mixing deposits and solids in rain spillway basin and pump sump
- → Breaking down of sludge layers
- → Agriculture
- → Water supply
- → Wet wells

#### Thrust

32-292 lbf (145-1300N)

#### **Features & Benefits**

- → Compact directly driven submersible mixer
- $\rightarrow$  Stationary installation on walls and floors
- → Can be swiveled vertically and horizontally for installation with lowering device
- → ATEX and FM versions
- $\rightarrow\,$  Self-cleaning propeller with helix hub
- $\rightarrow$  Easy-to-install propeller attachment

#### Wilo-TR(E)

Medium-Speed Submersible Mixers with Planetary Gear

#### Application

- → Creation of fluid current in activated sludge tanks
- → Suspension of solids
- → Prevention of floating sludge layers
- $\rightarrow$  Industry & Agriculture
- $\rightarrow$  Water supply
- $\rightarrow$  BNR

#### Thrust

25-1,025 lbf (110-4560N)

#### Features & Benefits

- → Flexible installation
- → Single-stage planetary gear for adjusting the propeller speed
- $\rightarrow$  Self-cleaning propeller
- $\rightarrow$  Easy-to-install propeller attachment
- → Type "TRE" with IE3 performance optimized motors
- → ATEX and FM versions

#### **Technical Data**

- → Submerged operating mode: S1 (continuous duty)
- $\rightarrow$  Max. temp: 104°F (40°C)
- → Protection class: IP 68
- → Permanently lubricated anti-friction bearing

#### Materials of Construction

- → Stainless Steel Motor Shaft
- → Stainless Steel Propeller
- → SiC/SiC Combination Mechanical Seal

#### **Technical Data**

- → Submerged operating mode: S1 (continuous duty)
- → Max. temp: 104°F (40°C)
- → Protection class: IP 68
- $\rightarrow$  Single-stage planetary gear
- → Permanently lubricated anti-friction bearing

#### **Materials of Construction**

- → Stainless Steel, PUR or PUR/GFK or PA6C Propeller
- $\rightarrow$  Stainless Steel Gear Shaft
- $\rightarrow$  SiC/SiC Combination Mechanical Seal



#### Wilo-TR(E)

Slow-Speed Submersible Mixers with Planetary Gear

#### Application

- → Mixing and circulation of activated sludge
- → Flow generation in water channels
- → Industry
- $\rightarrow$  Oxidation Ditches

#### Thrust

97-989 lbf (430-4400N)

#### **Features & Benefits**

- → Slow-running submersible mixer with twostage planetary gear
- → Flexible installation
- → 2-stage planetary gear for adjusting the propeller speed
- → Self-cleaning propeller
- → Propeller blades can be replaced individually
- → Easy-to-install blades and hub
- $\rightarrow$  ATEX and FM versions
- → "TRE" with IE3 performance optimized motors

#### **Technical Data**

- → Submerged operating mode: S1 (continuous duty)
- $\rightarrow$  Max. temp: 104°F (40°C)
- → Protection class: IP 68
- → Two-stage planetary gear with exchangeable second planetary stage
- $\rightarrow$  Permanently lubricated anti-friction bearing

#### Materials of Construction

- $\rightarrow$  GFK/VE or PA6C Propeller
- → Stainless Steel Gear Shaft
- $\rightarrow$  SiC/SiC Combination Mechanical Seal



wilo<sup>®</sup>

## Zetos ZK8 ZK10

## Best in class

#### **High-Efficiency Hydraulics**

The Zetos features multistage hydraulics with semi-axial impellers. Housing parts and impellers are made of precision-cast stainless steel. An optimised impeller design ensures highly smooth operation. The pressure connection is equipped with an integrated non-return valve.

Hydraulic Efficiency

#### **Customization is Key**

The individual configurability of the Zetos is clear when it comes to submersible motors. Powerful 6-inch and 8-inch drives with different strengths, tailored exactly for your applications. Available as an encapsulated variant for a high thermal load, as a rewindable variant for a wide range of configuration options or a highly efficient variant with a permanent magnet motor.



#### Groundwater

Submersible pumps for water supply from water wells, agriculture, dewatering, and industrial applications.









#### o S Certified to TSF/ANSI 61 & 372

#### Wilo-TWI

4" Stainless Steel Well Pumps



#### Application

- → Potable Water Supply
- $\rightarrow$  Irrigation
- $\rightarrow$  Municipal
- $\rightarrow$  Pressure Boosting
- → Agriculture
- → Industrial Process

#### Max. Flow

#### 110 GPM

- Max. Head
- 2,200 feet

#### **Features & Benefits**

- → Motors and pump ends certified to NSF/ANSI 61 listed with CSA
- $\rightarrow$  Vertical and horizontal installation possible
- $\rightarrow$  Motors up to 250 HP
- $\rightarrow\,$  Control boxes and VFD's available
- $\rightarrow$  NEMA standard mounting specs
- $\rightarrow$  High-quality shaft bearings
- $\rightarrow\,$  Check valve standard on all models
- $\rightarrow\,$  Stainless Steel construction
- $\rightarrow$  Additional models available on request

#### **Technical Data**

- → Electrical Connection: 1~115/230v 3~230/460/575v
- $\rightarrow$  Temp range: 37°F to 122°F (3°C to 50°C)
- → Max. Sand Content: 50 ppm
- $\rightarrow$  Max. Immersion Depth: 1000'
- $\rightarrow$  Protection Class: IP 68

#### **Materials of Construction**

- → Stainless Steel construction
- → Carbon/Graphite/PTFE Stop Ring
- → Stainless Steel/NBR Neck Ring
- → NBR Bearing

#### Wilo-TWU

4"- 6" Stainless Steel Well Pumps with Noryl Impellers



#### Application

- $\rightarrow$  Potable Water Supply
- → Irrigation
- → Municipal
- → Pressure Boosting
- → Agriculture
- → Industrial Process

#### Max. Flow

110 GPM

#### Max. Head

2,400 feet

#### Features & Benefits

- $\rightarrow$  Motors certified to NSF/ANSI 61 listed with CSA
- → Noryl impellers for maximum wear and abrasive resistance
- → High-quality shaft bearings for long life and easy installation
- $\rightarrow$  Optional VFD's and control boxes available
- → NEMA standard mounting specifications
- → Vertical and horizontal installation possible
- $\rightarrow$  Check valve standard on all models
- → Additional models available on request

#### **Technical Data**

- → Electrical Connection: 1~115/230v 3~230/460/575v
- $\rightarrow$  Temp range: 37°F to 95°F (3°C to 35°C)
- → Max. Sand Content: 50 ppm
- → Max. Immersion Depth: 1000'
- $\rightarrow$  Protection Class: IP 68

#### **Materials of Construction**

- → Stainless Steel construction
- → Noryl Impellers & Shaft Sleeve
- → Glass-filled Polycarbonate Bearing Spider & Diffuser
- $\rightarrow$  NBR O-Ring
- → Polyacetal Bearing

#### Wilo-SPI

6"- 10" Stainless Steel Well Pumps



#### Application

- → Potable Water Supply
- → Irrigation
- $\rightarrow$  Municipal
- → Pressure Boosting
- → Agriculture
- $\rightarrow$  Industrial Process

#### Max. Flow

- 1,400 GPM
- Max. Head
- 2,200 feet

#### Features & Benefits

- $\rightarrow$  Certified to NSF/ANSI 61 & 372
- → Vertical and horizontal installation possible

27

→ Motors up to 250 HP

**Technical Data** 

→ NBR Bearing

3~230/460/575v

→ Protection Class: IP 68
Materials of Construction

→ Max. Sand Content: 50 ppm

→ Max. Immersion Depth: 1000'

→ Carbon/Graphite/PTFE Stop Ring

→ Stainless Steel/NBR Neck Ring

- → Control boxes and VFD's available
- → NEMA standard mounting specs
- $\rightarrow$  High-quality shaft bearings
- → Check valve standard on all models
- → Stainless Steel construction
   → Additional models available on request

→ Electrical Connection: 1~115/230v

→ Temp range: 37°F to 122°F (3°C to 50°C)





#### Wilo 3HS-CP

3" High-Speed Submersible Pumps with Noryl Impellers



#### Application

- → Potable Water Supply
- $\rightarrow$  Irrigation
- $\rightarrow$  Municipal
- $\rightarrow$  Pressure Boosting
- → Agriculture
- → Industrial Process

#### Max. Flow

31 GPM

Max. Head

#### 475 feet

#### **Features & Benefits**

- → High-speed 8400 RPM rewindable motor
- → Available in Constant Pressure (CP) and
- Integrated (I) models
- ightarrow Integrated check valve
- ightarrow Frequency converter included on CP models
- $\rightarrow\,$  Vertical and horizontal installation possible

#### Technical Data

28

- → Electrical Connections: 1~230v
- → Temp Range: 37°F to 95°F (3°C to 35°C)
- $\rightarrow$  Max. sand content: 50 ppm
- → Max. immersion depth: 500'
- $\rightarrow$  Max number of starts: 30/h
- → Protection class: IP 58

#### **Materials of Construction**

- → 304 SS construction
- → Noryl Impellers

#### Wilo Quick Solar, Opti Solar

4" Solar Pumps



#### Application

- $\rightarrow$  Irrigation
- → Municipal
- → Pressure Boosting
- → Agriculture
- → Industrial Process

#### Max. Flow

48 GPM

#### Max. Head

#### 750 feet

#### **Features & Benefits**

- → Integrated inverter
- → Sophisticated dynamic MPPT algorithm
- → Integrated protection features
- $\rightarrow$  Integrated water level sensor
- → External control module (optional)
- $\rightarrow$  AC power cable input
- → Remote monitoring and operation

#### **Technical Data**

- → Quick Solar Electrical Connections: 70–190 VDC
- → Opti Solar Electrical Connections: 90–340 VDC or 90–265 VAC
- → Max. liquid temp: 92°F
- → Max. immersion depth: 500'
- → Protection class: IP 68
- → Kingsbury thrust bearing

#### **Materials of Construction**

- → AISI 304 SS construction
- → Helical rotor models have 316SS rotor



#### Wilo Submersible Motors

3-10" Motors

#### 4" Standard Submersible Motors

- $\rightarrow$  Certified to NSF / ANSI 61
- → Stainless Steel for maximum corrosion resistance
- → Coal Bed Methane Series available for aggressive applications
- → Equipped with surge arrestors on 115/230v models
- $\rightarrow$  Automatic thermal overload protection
- $\rightarrow$  Efficient 2-wire motors
- → Electrical Connections: 1~115/230v and 3~230/460/575v
- $\rightarrow$  Max. temp: 86°F (30°C)
- $\rightarrow$  48" cable length for ½-1½ HP models
- $\rightarrow$  100" cable length for 2+ HP models

#### 4 & 6" Standard Encapsulated Motors

- $\rightarrow$  H.D. Sand Sealing System (3S)
- $\rightarrow$  Dual flange for easy connection
- → 5-60 HP
- $\rightarrow$  Available in 3~ 230/460/575v
- $\rightarrow$  NEMA standard flange
- $\rightarrow$  Durable Stainless Steel motor housing
- → Available 2 or 3 wire connections
- $\rightarrow$  Max temp: 95°F (35°C)
- → IP68 insulation

#### 6"-10" Standard Submersible Motors

- $\rightarrow$  Electrical Connections:
- 3~230/460/575/1000v
- $\rightarrow$  NEMA standard flange
- → Standard temp: 95°F (35°C)
- → High temp:  $176^{\circ}F(80^{\circ}C)$

→ Rewindable motor stator

→ High-temp models available

 $\rightarrow$  Custom power cable lengths

configurations available

→ Optional PT100 thermistor

→ Water-filled design

 $\rightarrow$  High-guality thrust bearings

 $\rightarrow$  Voltages up to 6000v

- $\rightarrow$  NEMA splined shaft
- → pH 6.5-8.0
- $\rightarrow$  Durable Stainless Steel motor housing
- → 304 & 316 available

#### 6"-16" NU Rewindable Submersible Motors

→ Cast Iron, 304 Stainless Steel, 316 Stainless

Steel, Bronze, and Duplex Stainless Steel





#### **Wilo Submersible Accessories**

Control Boxes, Variable Frequency Drives, Pump Panels

#### **Control Boxes**

- $\rightarrow$  Standard
- $\rightarrow$  Deluxe
- → Deluxe CSCR
- $\rightarrow$  Deluxe (6")

#### Wilo Pump Panel

- → NEMA type 3R steel enclosure with powder coating finish
- → Full gasket hinged door with provision for padlocks
- → UL listed and suitable for use as service equipment
- → Heavy-duty flange fusible disconnect switch
- $\rightarrow$  NEMA Full voltage magnetic motor starter

#### Wilo MaxAir™

Hydropneumatic Pressure Tanks

#### Application

- → Water Storage
- → Water Pressure Boosting
- → Water Transfer

#### Max. Working Pressure

150 PSI

#### Max. Working Temperature

195°F

#### **Features & Benefits**

- → NSF/ANSI 61 compliant, IAPMO R&T UPC approved
- $\rightarrow$  Polypropylene liner to ensure long durabilty
- → Butyl diaphragm to assure long-life and safety
- → Corrosion-resistant durable baked epoxy coating
- $\rightarrow$  Leak-free, O-ring sealed air valve cap
- $\rightarrow$  100% pressure tested
- $\rightarrow$  No maintenance needed
- $\rightarrow$  304 Stainless Steel water connection



### A WILO BRAND

Pline

Scot's roots began as a provider to the agricultural industry, primarily for the transferring and spreading liquid fertilizers. Today, Scot has expanded their expertise to become a specialist in the manufacturing of close-coupled centrifugal pumps for the OEM, HVAC, military, and industrial markets. Scot's manufacturing facility in Cedarburg, Wisconsin is in the heartland of the some of the America's finest automated foundries, where quality castings and gray iron, bronze, stainless steel and aluminum are readily available.

Scot has a distributor network around North America which supports aftermarket and replacement demands by stocking most of the common parts and pumps they offer. Scot's commitment to quality and dedication to short lead times has cultivated a reputation of reliability and outstanding customer service.

Ft. Lauderdale, Florida is home to the Marine Division which provides all types of non-ferrous pumps and other solutions to yachts and commercial vessels.





#### Elite Cast Iron, Close-Coupled Pumps, 1750 RPM

Models: 602, 603, 604, 605, 701, 702, and 704



#### Application

- → Cooling Towers
- $\rightarrow$  Chillers
- $\rightarrow$  Plastic Injection Molding
- $\rightarrow$  Process Water Filtration & Circulation
- → Condensate Return
- → Heat Treating

#### Max. Flow

250 GPM

#### Max. Head

42 feet

#### **Features & Benefits**

- $\rightarrow$  Up to 2 HP and 3" Discharge
- $\rightarrow$  Heavy-duty construction
- $\rightarrow\,$  Close-coupled back pull-out design
- $\rightarrow$  Mechanical Seal

#### **Technical Data**

32

Scot Pump

- → NEMA 60HZ J56 Frame
- $\rightarrow$  ODP, TEFC, Explosion-proof enclosures
- $\rightarrow$  5.5"–6.5" Max Impeller
- → Temp range: 0°F to 250°F
- $\rightarrow$  Max working pressure: 175 PSI

#### **Materials of Construction**

- → NPT Connections
- → Standard Fitted
- → 600 Series: 304SS Impeller
- → 700 Series: Composite Impeller
- → All Iron
- → Buna Carbon Ceramic Seal standard
- → EPDM, Viton & Silicon Carbide available

#### Elite Cast Iron, Close-Coupled Pumps, 3500 RPM

Models: 501, 503, 471, and 481



#### Application

- → Cooling Towers
- $\rightarrow$  Chillers
- → Plastic Injection Molding
- → Process Water Filtration & Circulation
- → Condensate Return
- → Heat Treating

#### Max. Flow

#### 250 GPM

#### Max. Head

125 feet

#### **Features & Benefits**

- $\rightarrow$  Up to 5 HP and 2" Discharge
- → Heavy-duty construction
- → Close-coupled back pull-out design
   → Mechanical Seal

#### **Technical Data**

- → NEMA 60HZ J56 Frames
- $\rightarrow$  ODP, TEFC, Explosion-proof enclosures
- → 5½" Max Impeller
- → Temp range: 0°F to 250°F
- → Max working pressure: 150 PSI

#### **Materials of Construction**

- → NPT Connections
- → Standard Fitted
- → 400 Series: 304SS Impeller
- → 500 Series: Composite Impeller
- → All Iron
- → Buna Carbon Ceramic Seal standard
- → EPDM, Viton & Silicon Carbide available

## Elite Cast Iron, Close-Coupled

#### Pumps, 3500 RPM

Models: 602, 603, 604, 605, 701, 702, and 704



#### Application

- $\rightarrow$  Cooling Towers
- $\rightarrow$  Chillers
- → Plastic Injection Molding
- $\rightarrow\,$  Process Water Filtration & Circulation
- $\rightarrow$  Condensate Return
- $\rightarrow$  Heat Treating

#### Max. Flow

#### 450 GPM

- Max. Head
- 175 feet

#### **Features & Benefits**

- $\rightarrow$  Up to 15 HP and 3" Discharge
- $\rightarrow$  Heavy-duty construction
- → Close-coupled back pull-out design
- → Mechanical Seal

#### **Technical Data**

- → NEMA 60HZ, JM Frames
- $\rightarrow$  ODP, TEFC, Explosion-proof enclosures
- $\rightarrow$  6<sup>1</sup>/<sub>2</sub>" Max Impeller
- $\rightarrow$  Temp range: 0°F to 250°F
- → Max working pressure: 175 PSI

#### **Materials of Construction**

- → NPT Connections
- → Standard Fitted
- → 600 Series: 304SS Impeller
- → 700 Series: Composite Impeller

→ Buna Carbon Ceramic Seal standard

→ EPDM, Viton & Silicon Carbide available

 $\rightarrow$  All Iron





#### Cast Iron, Close-Coupled Pumps, 1150 RPM

Models: 57, 59, 96, 97, and 267



#### Application

→ Water Features

→ Water Parks

#### Max. Flow

4,500 GPM

#### Max. Head

60 feet

#### **Features & Benefits**

- $\rightarrow$  Up to 50 HP and 10" Discharge
- $\rightarrow$  Heavy–duty construction
- $\rightarrow$  Close-coupled back pull-out design
- $\rightarrow$  Mechanical Seal

#### **Technical Data**

- → NEMA 60HZ JM, JP, JPZ Frames
- $\rightarrow$  ODP, TEFC, Enclosures
- $\rightarrow$  6<sup>1</sup>/<sub>2</sub>" 13" Max Impeller
- → Temp range: 0°F to 250°F
- → Max working pressure: 175 PSI

#### **Materials of Construction**

- → ANSI Flange Connections
- → Standard Fitted
- → Bronze Fitted
- $\rightarrow$  All Iron
- → Buna Carbon Ceramic Seal standard
- $\rightarrow\,$  EPDM, Viton & Silicon Carbide available

#### Cast Iron, Close–Coupled Pumps, 1750 RPM

Models: 5½" C56/JM, 6½" C56/JM, 8" JP, 10" JP



#### Application

- $\rightarrow$  Cooling Towers
- $\rightarrow$  Chillers
- → Plastic Injection Molding
- $\rightarrow$  Process Water Filtration & Circulation
- → Condensate Return
- $\rightarrow$  Heat Treating

#### Max. Flow

#### 6,500 GPM

#### Max. Head

150 feet

#### **Features & Benefits**

- $\rightarrow$  Up to 150 HP and 10" Discharge
- $\rightarrow$  Heavy–duty construction
- → Close-coupled back pul-lout design
   → Mechanical Seal

#### **Technical Data**

- $\rightarrow$  NEMA 60HZ C56, JM, JP, JPZ Frames
- $\rightarrow$  ODP, TEFC, Explosion-proof enclosures
- $\rightarrow$  5<sup>1</sup>/<sub>2</sub>" 13" Max Impeller
- → Temp range: 0°F to 250°F
- → Max working pressure: 175 PSI

#### **Materials of Construction**

- → NPT and ANSI Flange Connections
- → Standard Fitted
- → Bronze
- → Fitted or All Iron
- → Buna Carbon Ceramic Seal standard
- $\rightarrow$  EPDM, Viton & Silicon Carbide available

#### Cast Iron, Close–Coupled Pumps, 3500 RPM

Models: 3½" J56, 5½" J56/JM, 6½" JM, 9" JM/JP



#### Application

- $\rightarrow$  Cooling Towers
- $\rightarrow$  Chillers
- $\rightarrow$  Plastic Injection Molding
- → Process Water Filtration & Circulation
- $\rightarrow$  Condensate Return
- $\rightarrow$  Heat Treating

#### Max. Flow

#### 1,750 GPM

- Max. Head
- 375 feet

#### **Features & Benefits**

- $\rightarrow$  Up to 100 HP and 8" Discharge
- $\rightarrow$  Heavy-duty construction
- $\rightarrow$  Close-coupled-back pull-out design
- $\rightarrow$  Mechanical Seal

#### **Technical Data**

- $\rightarrow$  NEMA 60HZ, J56, JM, JP Frames
- $\rightarrow$  ODP, TEFC, Explosion-proof enclosures
- $\rightarrow$  3<sup>1</sup>/<sub>2</sub>" 9" Max Impeller
- $\rightarrow$  Temp range: 0°F to 250°F
- → Max working pressure: 175 PSI

#### **Materials of Construction**

- → NPT and ANSI Flange Connections
- → Standard Fitted
- → Bronze Fitted
- → All Iron

- → Buna Carbon Ceramic Seal standard
- $\rightarrow\,$  EPDM, Viton & Silicon Carbide available

Scot Pump



#### Welded Stainless Steel, Close-Coupled Pumps, 3500 RPM

Models: Models: 320-328



#### Application

- → Booster Systems
- $\rightarrow$  Chillers
- → Plastic Injection Molding
- → Process Cooling Water
- → Dishwashing Equipment
- → Induction Heating / Cooling
- → Potable Water

#### Max. Flow

400 GPM

#### Max. Head

275 feet

#### **Features & Benefits**

- → NSF/ANSI 61 & 372 certified
- → Up to 25 HP and 2" Discharge
- → Cast Iron Adapter supports seal and prevents flexing of Pump
- → Close-coupled back pull-out design
- → Centerline Discharge
- → Mechanical Seal

#### **Technical Data**

34

Scot Pump

- $\rightarrow$  NEMA 60HZ J56, JM, TC Frames
- $\rightarrow$  ODP, TEFC, Explosion-proof enclosures
- → 4.50" 8.00" Max Impeller
- $\rightarrow$  Temp range: 0°F to 225°F
- → Max working pressure 175 PSI

#### Elite Cast 304 Stainless Steel, Close-Coupled Pumps, 3500 RPM

Models: 471S, 340 Series, 500S Series, and 700S Series



#### Application

- → Booster Systems
- $\rightarrow$  Chillers
- → Injection Molding Cooling
- → Process Cooling Water
- → Dishwashing Equipment
- → Induction Heating Cooling Water
- → Potable Water
- , i otable water

#### Max. Flow

#### 325 GPM

Max. Head

#### 175 feet

#### **Features & Benefits**

- → NSF/ANSI 61 & 372 certification pending
- $\rightarrow$  Up to 3 HP and 2" Discharge
- → Cast Iron Adapter supports seal and prevents flexing of Pump
- → Close-coupled back pull-out design
- → Mechanical Seal

#### **Technical Data**

- → NEMA 60HZ J56 Frames
- $\rightarrow$  ODP, TEFC, Explosion-proof enclosures
- $\rightarrow$  4.50" 6.50" Max Impeller
- → Temp range: 0°F to 225°F

**Materials of Construction** 

→ NPT Connections

→ Max working pressure 150 PSI

#### Materials of Construction

- → NPT and Flange Connections
- → 304 Stainless Steel Casing, Impeller and Seal Plate. Cast Iron Adapter
- → Buna Carbon Ceramic Seal standard
- → EPDM, Viton & Silicon Carbide available
- $\rightarrow$  340, 500, 700 Series: Composite Impeller

→ 400 Series: 304SS Impeller

- → Buna Carbon Ceramic Seal is standard
- $\rightarrow\,$  EPDM, Viton & Silicon Carbide available

→ 304 Stainless Steel Casing and Adapter

#### Elite Cast 316 Stainless Steel, Close-Coupled Pumps, 3500 RPM

Models: 13S, 602S, 604S, and 605S



#### Application

- $\rightarrow$  Chiller
- → Dishwashers
- → Washing Equipment
- → Process Cooling Water

#### Max. Flow

450 GPM

#### Max. Head

125 feet

#### **Features & Benefits**

- → NSF/ANSI 61 & 372 certification pending
- → Up to 15 HP and 3" Discharge
- $\rightarrow$  Heavy-duty construction
- $\rightarrow$  Close-coupled back pull-out design
- → Mechanical Seal

#### **Technical Data**

- $\rightarrow$  NEMA 60HZ J56, TC Frames
- $\rightarrow\,$  ODP, TEFC, Explosion–proof enclosures
- → 5.63" Max Impeller
- → Temp range:  $0^{\circ}$ F to 250°F
- → Max working pressure 175 PSI

#### **Materials of Construction**

- → NPT Connections
- $\rightarrow\,$  316 Stainless Steel wetted components
- → Viton Silicon Carbide Seal is standard





#### All Bronze, Close-Coupled Pumps 3500 RPM

Models: 5<sup>1</sup>/<sub>2</sub>" J56/JM, 6<sup>1</sup>/<sub>2</sub>" JM and 9" JM



#### Application

Max. Flow

1000 GPM

Max. Head

**Features & Benefits** 

→ Mechanical Seal

**Technical Data** 

 $\rightarrow$  Up to 40 HP and 3" Discharge

→ Close-coupled back pull-out design

 $\rightarrow$  ODP, TEFC, Explosion-proof enclosures

 $\rightarrow$  Heavy-duty construction

→ NEMA 60HZ J56, JM Frames

 $\rightarrow$  5.00" – 9.00" Max Impeller → Temp range: 0°F to 250°F

→ Max working pressure 175 PSI

375 feet

- → Induction Heating Cooling Water
- → Heat Exchanger
- → Pressure Boosting
- → Raw Water Supply



#### All Bronze, Close-Coupled Pumps 1750 RPM

Models: 51/2" C56/JM, 61/2" C56/JM and 9" JM



- → Induction Heating Cooling Water
- → Heat Exchanger
- → Water Recirculation Systems
- → Raw Water Supply

#### Max. Flow

500 GPM

#### Max. Head

95 feet

#### **Features & Benefits**

- $\rightarrow$  Up to 20 HP and 4" Discharge
- → Heavy-duty construction
- → Close-coupled back pull-out design
- → Mechanical Seal

#### **Technical Data**

- → NEMA 60HZ C56, JM Frames
- $\rightarrow$  ODP, TEFC, Explosion-proof enclosures
- → 5.50" 9.00" Max Impeller
- → Temp range: 0°F to 250°F
- $\rightarrow$  Max working pressure 175 PSI

→ 4.50" – 13.00" Max Impeller

→ Temp range: -30°F to 400°F

- **Materials of Construction**
- → NPT and Flange Connections
- → Standard Fitted
- → Bronze Fitted
- → All Bronze
- $\rightarrow$  All Iron
- → Cast 316SS

#### **Specialty Products**

Hot Oil, Low Temp Chiller, Self-Priming, Vertical Flange, Vertical Floor Mounted, Vertical Sealless

#### Application

- → Parts Washers
- → Condensate Return
- → Dewatering
- → Water Features  $\rightarrow$  Refrigeration
- → Heat Transfer

#### Max. Flow

6,000 GPM

Max. Head

180 feet

#### **Features & Benefits**

**Technical Data** 

 $\rightarrow$  Custom mounting configurations and features for unique applications

→ NEMA 60HZ J56, JM, JP, JPZ, TCZ Frames

 $\rightarrow$  ODP, TEFC, Explosion-proof enclosures

#### 35

Scot Pump

#### **Materials of Construction**

- → NPT and ANSI Flange Connections
- → 836 Bronze Case Impeller and Adapter
- → Buna Carbon Ceramic Seal is standard.
- → EPDM, Viton & Silicon Carbide available

#### **Materials of Construction**

- → NPT and ANSI Flange Connections
- → 836 Bronze Case Impeller and Adapter
- → Buna Carbon Ceramic Seal is standard
- → EPDM, Viton & Silicon Carbide available

Application





#### **MotorPump**<sup>™</sup>

Close-Coupled Pumps in Welded Stainless Steel, 3500 RPM



#### Application

- $\rightarrow$  Irrigation
- → Fertilization Transfer
- → Bulk Tank Systems
- → Potable Water

#### Max. Flow

#### 400 GPM

- Max. Head
- 275 feet

#### **Features & Benefits**

- → NSF/ANSI 61 & 372 certified
- $\rightarrow$  Up to 25 HP and 2" Discharge
- → Cast Iron Adapter supports seal and prevents flexing of pump
- → Close-coupled back pull-out design
- → Centerline Discharge
- → Mechanical Seal

#### **Technical Data**

- → NEMA 60HZ J56, JM Frames
- $\rightarrow$  ODP, TEFC, Explosion-proof enclosures
- → 4.50" 8.00" Max Impeller
- → Temp range: 0F to 225°F
- → Max working pressure: 175 PSI

#### **Materials of Construction**

- → NPT and Flange Connections
- → 304 Stainless Steel Casing, Impeller and Seal Plate. Cast Iron Adapter
- → Viton Carbon Ceramic Seals standard, Viton SiC/SiC available

#### MotorPump<sup>™</sup> Elite Series

Close-Coupled Pumps in Cast 304 Stainless Steel, 3500 RPM



#### Application

#### → Irrigation

- → Fertilization Transfer
- → Bulk Tank Systems

#### Max. Flow

#### 450 GPM

- Max. Head
- 120 feet

#### **Features & Benefits**

- $\rightarrow$  Up to 15 HP and 3" Discharge
- → Cast 304 or 316 Stainless Steel construction
- → Close-coupled back pull-out design

#### **Technical Data**

- → NEMA 60HZ J56, TC Frames
- → TEFC, Explosion-proof enclosures
- → 4.50" 5.5" Max Impeller
- → Max working pressure: 175 PSI

#### Materials of Construction

- → NPT Connections Standard
- → 304/316 Stainless Steel Casing and Adapter
- $\rightarrow$  Composite or 304/316 Impellers
- → Viton Carbon Ceramic Seal on 304SS models, Viton SiC/SiC on 316SS models



#### MotorPump<sup>™</sup> Elite Series

Close-Coupled Pumps in Cast 316 Stainless Steel, 3500 RPM



#### Application

- $\rightarrow$  Irrigation
- → Fertilization Transfer
- → Bulk Tank Systems

#### Max. Flow

#### 2.500 GPM

Max. Head

375 feet

#### **Features & Benefits**

- $\rightarrow$  Up to 100 HP and 6" Discharge
- $\rightarrow$  Heavy-duty Cast Iron construction
- → Close-coupled back pull-out design

#### **Technical Data**

- → NEMA 60HZ J56, JM, JP Frames
- → TEFC, Explosion-proof enclosures
- → 4.50" 11.00" Max Impeller
- → Max working pressure: 175 PSI

#### **Materials of Construction**

- → NPT and Flange Connections
- → All Cast Iron construction
- → Viton Carbon Ceramic Seal standard
- → Viton SiC/SiC Mechanical Seals optional



Scot Pump-Agricultural





#### **MotorPump™ LFE Series**

Cast Iron, Close-Coupled Pumps 1750/3500 RPM



#### Application

- $\rightarrow$  Irrigation
- → Fertilization Transfer
- → Bulk Tank Systems

#### Max. Flow

- 2500 GPM
- Max. Head

#### 375 feet

#### **Features & Benefits**

- $\rightarrow$  Up to 100 HP and 6" Discharge
- → Heavy-duty Cast Iron construction
- → Close-coupled back pull-out design

#### FramePumps™

Models: FPH, FPD, FP, Pressure Seal



#### → Sprayer Systems

- → Bulk Tank Systems
- → Fertilizer Transfer

#### Max. Flow

2500 GPM

#### Max. Head

400 feet

**Technical Data** 

- **Features & Benefits**
- $\rightarrow$  Heavy-duty bearing Frames

 $\rightarrow$  Drive shafts 5/8" to 1 3/8"

**Materials of Construction** 

→ Pully, PTO, Hydraulic or Clutch

 $\rightarrow$  Pressure Seal doubled sealed with 50/50 water glycol solution

#### **Technical Data**

- → Suction Lift 25'
  - → NEMA 60Hz J56, JM Frame
  - → TEFC Motors

#### **Materials of Construction**

- $\rightarrow$  Cast Iron or Stainless Steel construction
- → Viton Carbon Ceramic Mechanical Seal

37

- $\rightarrow$  Cast Iron or 316 Stainless Steel → Viton Carbon Ceramic Mechanical Seal, other
- options available

MotorPump<sup>™</sup>, EnginePump<sup>™</sup> Self-Priming Pumps, End Gun Booster H[ft]



#### Application

- → Portable Utility
- → Fertilizer Transfer
- $\rightarrow$  Irrigation
- → Nurse Tank Applications

#### Max. Flow

400 GPM

- Max. Head
- 140 feet

#### **Features & Benefits**

- $\rightarrow$  Self-Priming design
- → EnginePump<sup>™</sup> uses Honda<sup>®</sup> OHC Engines
- → Pump kits (less engine) available

**Technical Data** 

- $\rightarrow$  NEMA 60HZ J56, JM, JP Frames
- $\rightarrow$  TEFC, Explosion-proof enclosures
- → 4.50" 11.00" Max Impeller
- → Max working pressure 175 PSI

#### **Materials of Construction**

- → NPT and Flange Connections
- → All Cast Iron construction
- → Viton Carbon Ceramic Seal standard
- $\rightarrow$  Viton SiC/SiC Mechanical Seals optional

Application







#### **Marine Straight Centrifugal Pumps**

Scot Marine Straight

Centrifugal Pumps

35070

80

60

35000 Series

нíft

50

40

30 35066

20

0 . 0 35068

35069

Application

20

→ Air Conditioning

→ Cooling Water Circulation

 $\rightarrow$  Refrigeration

35064, 35065

40

#### Marine Straight Centrifugal Pumps

Scot Marine Straight

90 100 Q[G

Centrifugal Pumps

3500 RPM 60 Hz - No

48451

48000 Series

48372

Hĺft

90

80

70

60 50

40

30

20

10

100 Q[G

0 -

Application

→ Air Conditioning
 → Refrigeration

→ Cooling Water Circulation



57000 Series



#### Application

- → Air Conditioning
- $\rightarrow$  Refrigeration
- → Chilled Water Circulation

Max. Flow

90 GPM

#### Max. Head

48 feet

#### **Features & Benefits**

- $\rightarrow$  Heavy-duty cast construction
- → Close-coupled back pull-out design
- → Enclosed & Semi-open impeller
- → Continuous duty motor

#### **Technical Data**

- → NEMA 50/60HZ Motors
- $\rightarrow$  TEFC Motor is standard
- $\rightarrow$  NPT Connections

#### Materials of Construction

 $\rightarrow\,$  Marine Bronze Case, Impeller and Adapter

#### Max. Flow

#### 110 GPM

#### Max. Head

90 feet

#### **Features & Benefits**

- → Heavy-duty cast construction
- → Close-coupled back pull-out design
- → Semi-open impeller
- → Continuous duty motor

#### **Technical Data**

- → NEMA 50/60HZ Motors
- → TEFC Motor is standard
- → NPT Connections

#### Materials of Construction

 $\rightarrow$  Marine Bronze Case, Impeller and Adapter

#### Max. Flow

400 GPM

#### Max. Head

130 feet

#### **Features & Benefits**

- → Heavy-duty cast construction
- → Close-coupled back pull-out design
- → Enclosed & Semi-open impeller
- → Continuous duty motor

#### **Technical Data**

- → NEMA 50/60HZ Motors
- → TEFC Motor is standard
- $\rightarrow$  NPT Connections

#### **Materials of Construction**

→ Marine Bronze Case, Impeller and Adapter

Scot Pump





#### Marine Sewage & Wastewater Centrifugal Pumps

48382 Series



#### Application

Max. Flow

100 GPM

50 feet

Max. Head

**Features & Benefits** 

→ Vortex Impeller
 → Continuous duty motor

**Technical Data** 

→ Heavy-duty cast construction

 $\rightarrow$  Close-coupled back pull-out design

- → Sewage Transfer
- $\rightarrow$  Wastewater

#### Marine Self-Priming Centrifugal Pumps

48000 and 68000 Series



#### Application

- → Raw Water Intake
- $\rightarrow$  Air Conditioning
- $\rightarrow$  Refrigeration
- → Bilge/Ballast
- $\rightarrow$  Fire Fighting/Washdown

#### Max. Flow

200 GPM

#### Max. Head

100 feet

#### Features & Benefits

- → Heavy-duty cast construction
- → Close-coupled back pull-out design
- → Enclosed & Semi-open impeller
- $\rightarrow$  Self-Priming up to 20' lift
- → Continuous duty motor

**Technical Data** 

- $\rightarrow$  NEMA 50/60HZ Motors
- $\rightarrow$  TEFC Motor is standard
- $\rightarrow$  2" NPT Connections

#### **Materials of Construction**

 $\rightarrow\,$  Marine Bronze Case, Impeller and Adapter

#### → NEMA 50/60HZ Motors

- → TEFC Motor is standard
- $\rightarrow$  NPT Connections

#### Materials of Construction

 $\rightarrow$  Marine Bronze Case, Impeller and Adapter



#### **Marine Vented Loops**

#### 20913 Series

#### Models and Sizes Vented Loop with Vaccum Breaker

Loop Model No.	Size-D	Wt. (Lbs.)	Includes Vacuum Breaker Item			
20913-VL-05	1/2	0.05	20913-VB-18F			
20913-VL-06	5/8	0.06	20913-VB-18F			
20913-VL-07	3/4	0.07	20913-VB-18F			
20913-VL-09*	7/8	1.00	20913-VB-18F			
20913-VL-10	1	1.10	20913-VB-18F			
20913-VL-11**	1-1/8	1.20	20913-VB-38			
20913-VL-15	1-1/2	1.30	20913-VB-38			
20913-VL-20	2	1.70	20913-VB-38			
*Same as 1/2" pipe O.D.						

\*\*Fits rule bilge pump hose

#### Application

- → Head Flushing Discharge Line
- $\rightarrow$  Engine Wet Exhaust Line
- → Bilge Pump Out Line

#### **Features & Benefits**

- → Stops Back Siphonage
- $\rightarrow$  Sizes 1/2"-2"
- $\rightarrow\,$  SAE Hose Barb Connection

→ Delrin Vacuum Breaker Included

#### $\rightarrow$ Corrosion-proof construction

**Technical Data** 

#### **Materials of Construction**

 $\rightarrow$  316 Stainless Steel

Packaged Booster Systems



#### **Opti-Boost Max**

1-4 Pump Pressure Boosting Systems





Scot Opti-Boost Max

#### Application

- → Water Supply
- → Pressure Boosting
- → Agriculture
- → Washing/Sprinkling Systems
- $\rightarrow$  Cooling Circuits
- → Condensate Return

#### Max. Flow

1,578 GPM

#### Max. Head

807 feet

#### **Features & Benefits**

- → High efficient EC motor (IE5)
- → Real-time diagnostics and remote monitoring
- $\rightarrow$  Full system kWh energy reporting
- → Easy to use 7" touchscreen interface
- → Onboard Modbus and optional BACnet<sup>™</sup>, LonWorks<sup>®</sup> interface modules
- → Variable speed control per pump
- → Adjustable low pressure cut-out
- → Balanced run time for all pumps

#### **Technical Data**

40

Scot Pump

- $\rightarrow$  Fluid temp. range: -22°F to 248°F (-30°C to 120°C)
- → Electrical Connections: 3~460V
- → Rated pressure: 232 or 363 PSI depending on number of pump stages
- → System Connection: 150 or 300 Class ANSI flanges depending on maximum system pressure
- → TEFC motors standard

#### **Materials of Construction**

- → All 304 Stainless Steel construction
- → Entire packaged systems are listed under UL for NSF/ANSI 61
- → Entire packaged systems are listed under UL for QCZJ "packaged pumping systems".
- → EPDM/FKM Elastomers
- → Mechanical Seal options: Tungsten Carbide/ EPDM, or optional Viton®/FKM

1-Pump 100 50 3-Pum 4-Pump

800 1000 1200 1400 1600 Q[GPM]

(ŲL) us LISTED

#### Application

1-Pump

200 400 600

200

100

0

- → Water Supply
- → Pressure Boosting
- → Agriculture
- → Washing/Sprinkling Systems

2-Pump

- → Cooling Circuits
- → Condensate Return

#### Max. Flow

- 1,600 GPM
- Max. Head

#### 580 feet

#### **Features & Benefits**

- → Real-time diagnostics and remote monitoring
- $\rightarrow$  Full system kWh energy reporting
- → Easy to use 7" touchscreen interface
- → Onboard Modbus and optional BACnet<sup>™</sup>, LonWorks<sup>®</sup> interface
- → Variable speed control per pump
- → Adjustable low pressure cut-out
- → Balanced run time for all pumps

#### **Technical Data**

- $\rightarrow$  Fluid temp. range: -4°F to 248°F (-20°C to 120°C) with a minimum of 32°F for domestic water
- → Electrical Connections: 3~208-230/460/575V
- → Rated pressure: 232/363 PSI
- → Flange Connection: 150 Class ANSI
- → TEFC motors standard
- **Materials of Construction**
- → All 304 Stainless Steel construction
- → Entire packaged systems are listed under UL for NSF 61 and NSF 372
- → Entire packaged systems are listed under UL for QCZJ "packaged pumping systems"
- → EPDM/FKM Elastomers
- → Mechanical Seal options: Tungsten Carbide/ EPDM, or optional Viton®/FKM

#### Centri-Boost Max

1-4 Pump Pressure Boosting Systems



#### Application

- → Water Supply
- → Pressure Boosting
- → Agriculture
- → Washing/Sprinkling Systems
- → Cooling Circuits
- → Condensate Return

#### Max. Flow

1,600 GPM

#### Max. Head

275 feet

#### Features & Benefits

- → Includes Scot 320–328 series Stainless Steel pumps
- → Real-time diagnostics and remote monitoring
- → Full system kWh energy reporting
- → Easy to use 7" touchscreen interface
- → Onboard Modbus, and optional BACnet<sup>™</sup>, LonWorks® interface modules
- → Adjustable low pressure cut-out
- → Balanced run time for all pumps

#### **Technical Data**

 $\rightarrow$  Fluid temp. range: -4°F to 140°F (-20°C to 60°C) with a minimum of 32°F for domestic water

→ All wetted components are of 304 Stainless

→ Entire packaged systems are listed under UL

→ Entire packaged systems are listed under UL

for QCZJ "packaged pumping systems"

- → Premium efficient NEMA motors
- $\rightarrow$  VFD-Controlled system operation
- → 4-20 mA, ¼" Stainless Steel Pressure Transducers
- → Rated pressure: 150 PSI
- → Flange Connection: 150 Class ANSI

#### Materials of Construction

for NSF 61 and NSF 372

→ EPDM/FKM Elastomers

→ Type 21 Mechanical Seal

Steel construction





#### MVI

High-Pressure Vertical Multistage Centrifugal Pumps



#### Application

- → Water Supply
- $\rightarrow$  Pressure Boosting
- $\rightarrow$  Industrial Circulation Systems
- $\rightarrow$  Process Water
- $\rightarrow$  Cooling Water Circulation Systems
- $\rightarrow$  Washing Systems
- $\rightarrow$  Irrigation

#### Max. Flow

800 GPM

#### Max. Head

950 feet

#### Features & Benefits

- → Non-self-priming, high pressure, vertical multistage centrifugal pump with inline connections
- → The MVI is equipped with cartridge mechanical seal which enables quick and easy maintenance
- → The spacer coupling allows the mechanical seal to be replaced without removing the motor
- → The MVI series is also available with variable frequency drive upon request

#### **Technical Data**

- $\rightarrow$  NSF/ANSI 372 and 61 certified
- $\rightarrow$  Power connections: 1~115/230 V
- 3~ 230/460/575 V → Fluid temperature range determined by liquid type
- $\rightarrow$  Ambient temperature: 5°F to 104°F
- → Max. operating pressure: 145 PSI, 232 PSI, 363 PSI and 435 PSI (Depending on number of stages)

#### **Materials of Construction**

- $\rightarrow$  ANSI CLASS flanges connection
- $\rightarrow\,$  304 and 316 stainless steel construction
- $\rightarrow\,$  Stainless steel impellers, chambers, and casing

## WEIL Pump

A WILO BRAND

Weil has long been at the forefront in the design and manufacturing of centrifugal pumps for construction, industrial, commercial and municipal applications.

Dedicated to building a product that engineers can specify and contractors can sell and install with confidence, quality has always come first. In addition to pumps, Weil manufactures removal systems and controls, ensuring single-source accountability and trouble-free start-up and operation.

Weil's insistence on high-quality, rugged designs ensures the least maintenance over the life of the pump and yields the lowest lifecycle cost of any pump available. Additionally, Weil has an exclusive, national network of sales representatives whose interests and efforts continue even after the sale.





#### **Single Seal Submersible Sump Pumps**

Series 1400



#### Application

- → Elevator Pits
- → Below Ground Vaults
- → Process Water
- → Storm Water
- $\rightarrow$  Runoff
- → Drainage

#### Max, Flow

165 GPM

Max. Head

#### 105 feet

#### **Features & Benefits**

- → Long-duty life
- → Heavy-duty, rugged, industrial grade construction
- → Air-filled motor
- → NPT/ANSI Flange and discharge connections
- → Customizable construction

#### **Technical Data**

- → Class F Insulation
- → Double-sealed ball bearings
- $\rightarrow$  Up to 180°F operation
- → Copper Motor windings
- $\rightarrow$   $\frac{1}{2}$  to 2 HP
- → 1 & 3 phase, 115/208-230/460 Volts

#### **Materials of Construction**

- $\rightarrow$  Cast Iron–standard
- → Optional bronze or 316 Stainless Steel Impellers
- → SOOW Cable
- → Buna/Viton Seals and O-rings

#### Single Seal Submersibl Sewage **Pumps**

#### Series 2400



#### Application

- $\rightarrow$  Below ground vaults
- → Effluent & Wastewater
- → Clear and Grey water with solids, ideal for sewage pits

#### Max, Flow

#### 260 GPM

#### Max. Head

85 feet

#### **Features & Benefits**

- → Heavy-duty, rugged construction floor mount or quick removal style
- $\rightarrow$  Long-duty life
- → Air-filled motor
- → Customizable options

#### **Technical Data**

- → Class F Insulation
- → Thick gauge copper windings
- $\rightarrow$  Type 21 mechanical seal
- → Double-sealed ball bearings
- → SOOW power and sensor cable
- $\rightarrow$   $\frac{1}{2}$  to 2  $\frac{1}{2}$  HP
- → 1 & 3 phase 115/208-230/460 Volts

#### **Materials of Construction**

- → Cast Iron motor and pump housings
- → Optional bronze and 316 Stainless Steel Impellers and 316 Stainless Steel cases
- → Buna/Viton Seals and O-rings
- → Stainless hardware



#### **Single Seal Submersible Grinder** Pumps

#### Series 2400



#### Application

- $\rightarrow$  Residential sewage basins
- → Commercial & Industrial sewage pit
- → Underground Vaults
- → Process water with debris

#### Max. Flow

125 GPM

#### Max. Head

100 feet

#### **Features & Benefits**

- $\rightarrow$  Reduces sewage solids and debris to 3/8" diameter or less
- → Long-life Stainless Steel cutting components hardened to Rockwell 58C

#### **Technical Data**

- → Class F Insulation
- → Thick gauge copper windings
- $\rightarrow$  Type 21 mechanical seal
- → Double-sealed ball bearings
- → SOOW power and sensor cable
- $\rightarrow$   $\frac{1}{2}$  to 2  $\frac{1}{2}$  HP
- → 1 & 3 phase 115/208-230/460 Volts

#### **Materials of Construction**

- → Cast Iron motor and pump housings
  - → Optional bronze and 316 Stainless Steel Impellers and 316 Stainess Steel cases
  - → Buna/Viton Seals and O-rings

Weil Pump



- → Optional 316 Stainless Steel cases





#### **Double Seal Submersible Sump Pumps**

Series 1600



#### Application

- → Commercial & Industrial Pits
- → Pump Clear and Grey Water
- → Effluent & Wastewater with some solids
- → Loading docks, washdown, parking lots, flood vaults

#### Max. Flow

675 GPM

#### Max. Head

145 feet

#### Features & Benefits

- → Double-sealed ball bearings
- → Heavy-duty, rugged, cast iron construction
- $\rightarrow$  Long-duty life
- → Double-mechanical seal –type 21
- → UL/CUL listed explosion-proof designs for class 1, div 1 applications

#### **Technical Data**

- → Class F Insulation
- → Thick gauge copper windings
- → Double-sealed ball bearings
- → SOOW power and sensor cable
- → 1/2 to 15 HP
- → 1 & 3 phase 115/208-230/460/575 Volts

#### **Materials of Construction**

- $\rightarrow$  Cast Iron motor and pump housings
- → Optional bronze and 316 Stainless Steel Impellers and 316 Stainless Steel cases
- $\rightarrow$  Buna/Viton Seals and O-rings
- → Stainless hardware

#### **Double Seal Submersible Sewage Pumps**

#### Series 2500



#### Application

- $\rightarrow$  Passes sewage/solids up to 4" diameter for use in sanitary, wastewater, effluent process fluids
- → Vaults and pits, stormwater/runoff, flood

Max. Flow

#### 2,500 GPM

Max Head

#### 155 feet

#### Features & Benefits

- → Semi-open and enclosed impeller designs
- → Double-sealed ball bearings
- → Heavy-duty, rugged, cast iron construction
- → Long-duty life
- → Double-mechanical seal –type 21
- $\rightarrow$  UL/CUL listed explosion-proof designs for class 1, div 1 applications

#### **Technical Data**

- → Class F Insulation
- → Thick gauge copper windings
- → Double-sealed ball bearings
- → SOOW power and sensor cable
- → 1/2 to 50 HP 50-60hz
- $\rightarrow$  1 and 3 phase 115/208–230/460/575 Volt
- → 1150/1750/3500 RPM

#### **Materials of Construction**

- $\rightarrow$  Cast Iron motor and pump housings
- → Optional bronze and 316 Stainless Steel Impellers and 316 Stainless Steel cases
- → Buna/Viton Seals and O-rings
- → Stainless hardware

#### **Double Seal Submersible Grinder Pumps**



#### Application

 $\rightarrow$  Residential sewage basins, commercial and industrial sewage pit, underground vaults, process water with debris

#### Max. Flow

660 GPM

Max. Head

135 feet

#### Features & Benefits

- $\rightarrow$  Reduces sewage solids and debris to 3/8" diameter or less
- → Long-life Stainless Steel cutting components hardened to Rockwell 58C
- $\rightarrow$  Double-mechanical seal-type 21
- $\rightarrow$  UL/CUL listed explosion-proof designs for class 1, div 1 applications
- $\rightarrow$  440 C stainless Grinder/Cutter components

#### **Technical Data**

- → Class F Insulation
- → Thick gauge copper windings
- → Double-sealed ball bearings
- → SOOW power and sensor cable
- $\rightarrow$  3/4 to 6 HP
- → 1 & 3 phase 115/208-230/460/575 Volts

#### **Materials of Construction**

- $\rightarrow$  Cast Iron motor and pump housings
- → Optional bronze and 316 Stainless Steel Impellers and 316 Stainless Steel cases
- → Buna/Viton seals and O-rings

Series 2500









#### **Double Seal Submersible Stainless Pumps**

Series 1600S, 2500S



#### Application

 $\rightarrow$  Leachate drainage, brackish water, hospital sumps, laboratory waste, chemical process/ waste

#### Max. Flow

#### 425 GPM

Max. Head

#### 135 feet

#### **Features & Benefits**

- → Quick remove or floor mount 316 Stainless Steel sump, sewage, grinder pumps 1.25-3" discharge
- $\rightarrow$  Semi-open and enclosed impeller designs
- → Double-sealed ball bearings
- → Heavy-duty, rugged, cast iron construction
- → Long-duty life
- → Double mechanical seal –type 21
- → UL/CUL listed explosion-proof designs for class 1, div 1 applications

#### **Technical Data**

- → ½ 6 HP 50/60 hz
- → 1 & 3 phase 115/208-230/460/575 Volt
- → 1150, 1750, 3500 RPM
- → Viton Seals and O-rings
- → STOOW Chemical-resistant cable

#### **Materials of Construction**

→ All 316 Stainless Steel castings for pump and motor housings

#### **Vertical Sump Pumps**

#### Series 1100, 1200, 1300



#### Application

- $\rightarrow$  Residential, commercial, industrial sump pits, process fluids, underground vaults
- $\rightarrow$  Clear and grey water with small strained solids

#### Max. Flow

675 GPM

#### Max. Head

155 feet

#### **Features & Benefits**

- → Column style clear/grey water sump pumps in 1.25-4" discharge

- → Customizable construction
- → NEMA C-Face TEFC Motor
- bearing housings
- → Precision machined and polished shaft

#### **Technical Data**

- → ½-15 HP 50/60hz
- → 1 & 3 phase 115/208-230/460/575 Volt
- → 1150, 1750, 3500 RPM

#### **Materials of Construction**

- $\rightarrow$  Cast Iron pump and bearing housings
- → Optional bronze impeller
- → Bronze sleeve bearings-grease lubricated
- $\rightarrow$  Double-sealed ball thrust bearing
- → Galvanized column legs, pipe, and floor plate

#### Vertical Sewage Pumps

#### Series 2100, 2200



#### Application

- $\rightarrow$  Passes sewage/solids up to 4" diameter for use in sanitary, wastewater, effluent process fluids
- → Vaults and pits, stormwater/runoff, flood

#### Max. Flow

#### 875 GPM

- Max. Head
- 130 feet

#### **Features & Benefits**

- → Column style sewage/solids handling pumps in 2-6" discharge
- $\rightarrow$  2ft 16ft build lengths
- → Flexible coupled
- → Customizable construction
- → NEMA C-Face TEFC Motor
- $\rightarrow$  Heavy-duty, rugged, cast iron pump and bearing housings
- → Precision machined and polished shaft

#### **Technical Data**

- → ½-30HP 50/60hz
- → 1 & 3 phase 115/208-230/460/575 volts
- → 1150/1750 RPM

#### **Materials of Construction**

- → Cast Iron pump and bearing housings
- → Optional bronze impeller
- → Bronze sleeve bearings-grease lubricated
- → Double-sealed ball thrust bearing
- $\rightarrow$  Galvanized column legs, pipe, and floor plate

Weil Pump

46

 $\rightarrow$  2ft – 16ft build lengths  $\rightarrow$  Flexible coupled

→ Heavy-duty, rugged, cast iron pump and

Vertical Sump & Sewage



#### **Vertical Grinder Pumps**

Series 2100



#### Application

→ Residential sewage basins, commercial and industrial sewage pit, underground vaults, process water with debris

#### Max. Flow

#### 90 GPM

#### Max. Head

34 feet

#### **Features & Benefits**

- $\rightarrow$  Column style sewage/solids grinder pump -2" discharge
- → Reduces sewage solids and debris to 3/8" diameter or less
- → Long-life Stainless Steel cutting components hardened to Rockwell 58C

#### **Technical Data**

- → ½-5HP 60/60hz
- → 1 & 3 phase 115-208-230/460/575 Volt
- → 1750-3500RPM

#### **Vertical Stainless Pumps** Series 1200S, 1300S, 2100S



#### Application

 $\rightarrow$  Leachate drainage, brackish water, hospital sumps, laboratory waste, chemical process/ waste

#### Max. Flow

#### 425 GPM

- Max. Head
- 110 feet

#### **Features & Benefits**

- → Column Style 316 Stainless Steel Sump/ Sewage/Grinder pumps in 1.25-3" discharge
- → Heavy-duty grade 316 Stainless Steel cast components to withstand wet and corrosive environments
- → NEMA C Face TEFC motor

#### **Technical Data**

- → ½-6HP 50-60hz
- → 1 & 3 phase 115/208-230/460/575 Volts

#### → 1150, 1750, 3500 RPM

#### **Materials of Construction**

- $\rightarrow$  Cast Iron pump and bearing housings
- → Optional bronze impeller
- $\rightarrow$  Bronze sleeve bearings –grease lubricated
- → Double-sealed ball thrust bearing
- → Galvanized column legs, pipe, and floor plate
- → 440C Stainless Steel Grinder/Cutter components

#### **Materials of Construction**

- housings → Graphite sleeve bearings
- → 316 Stainless Steel column legs and discharge pipe

→ 316 Stainless Steel cast pump and bearing

→ Galvanized floor plates

#### **Materials of Construction**

- → 416 Stainless Steel shaft
- $\rightarrow$  Graphite sleeve bearings
- → Bronze enclosed impeller
- $\rightarrow$  Heavy-duty, rugged, cast pump housings/ bearings

#### **Vertical Condensate Pumps**

Series 4500



#### Application

 $\rightarrow$  Hot water condensate (210°F), cold water condensate, moderate acidic or alkaline process water, grease-free pits

#### Max. Flow

600 GPM

#### Max. Head

175 feet

#### **Features & Benefits**

- → Column style clear condensate water pump in 1.5-3" discharge
- → Stainless Steel shaft, bronze impeller, and graphite sleeve bearings able to withstand high temperatures and slightly corrosive environments
- → NEMA C Face TEFC motor

#### **Technical Data**

- → ½-5HP 50/60hz
- → 1 & 3 phase 115/208-230/460/575 Volts
- → 1150, 1750, 3500 RPM Motor









#### **Dry Well Wastewater Pumps**

Series 2800



#### Application

 $\rightarrow$  Above ground tank with pipe connection, clear or grey water collection tanks, sewage and solids tanks, where pump and motor must be easily visible and accessible

#### Max. Flow

1,300 GPM

#### Max. Head

185 feet

#### **Features & Benefits**

- $\rightarrow$  Close-coupled end suction sump/sewage pumps
- → Close-coupled back pull-out design, horizontal or vertical mount, sump sewage, and grinder models

#### **Technical Data**

- → NEMA JM frame TEFC motor
- $\rightarrow$  ANSI flange and NPT connections
- → 2-4" discharge
- → ¾-10HP 50/60hz
- → 1 & 3 phase, 115-208-230/460/575 Volt
- → Type 21 mechanical seal

#### **Materials of Construction**

- → Cast Iron pump construction
- $\rightarrow$  Bronze and Stainless Steel options
- → Bronze or Stainless Steel shaft sleeve
- $\rightarrow$  Buna mechanical seal and O-rings

#### **Dry Well Grinder Pumps**

#### Series 2800



 $\rightarrow$  Above ground tank with pipe connection, clear or grey water collection tanks, sewage and solids tanks, where pump and motor must be easily visible and accessible

M	ax	FI	OW

#### 660 GPM

#### Max. Head

135 feet

#### **Features & Benefits**

- $\rightarrow$  Close-coupled end suction grinder pump 2" discharge
- → Close-coupled back pull-out design, horizontal or vertical mount, sump sewage and grinder models

#### **Technical Data**

- → Nema JM Frame TEFC motor
- → 1-7.5HP 50/60hz
- → 1750, 3500 RPM
- → 1 & 3 phase 115/208-230/460/575 Volt
- → Type 21 mechanical seal

#### **Materials of Construction**

- → Cast Iron pump construction
- → Bronze and Stainless Steel options
- → Bronze or Stainless Steel shaft sleeve
- $\rightarrow$  Buna mechanical seal and O-rings
- → 440C Stainless Steel Grinder/Cutter components



#### **Pump Accessories**

Series 2600

#### Includes:

- → Quick Removals
- → Valve Systems
- → Reverse Flow Systems
- → Flush Valve

#### Application

 $\rightarrow$  Sump and sewage pit, fiberglass basins, concrete vault

#### Max. Flow

#### N/A

Max. Head

#### N/A

#### **Features & Benefits**

→ Quick removal systems and accessories → Facilitate the installation and removal of submersible sump, sewage, grinder, and vortex pumps

#### **Technical Data**

- → Simplex and duplex sub base plate
- $\rightarrow\,$  Simplex and duplex floor elbows and sliding brackets
- $\rightarrow$  Floor elbow and flange kits

#### **Materials of Construction**

- → Cast Iron standard
- → Bronze sliding brackets-optional
- → 316 stainless systems-optional cast



Weil Packaged Systems



#### **Packaged Systems**

Series 2640

#### Includes:

- → Basin
- → Basin cover
- → Sub base
- → Removal system
- $\rightarrow$  Pumps
- $\rightarrow$  Valves
- → Piping
- → Floats
- $\rightarrow$  Junction box
- → Control panel

#### Application

- → Below ground sump and sewage pits
- → Below cover or through-cover designs

#### Max. Flow

#### N/A

#### Max. Head

N/A

#### Features & Benefits

- $\rightarrow\,$  Fiberglass basin package systems with pumps, valves, piping, and cover
- → Thick-walled basin with anti-float flange and lift lugs
- → Studded for quick remove systems
- → Discharge coupling plates

#### **Technical Data**

- → Through sidewall bolted plates for discharge and electrical cables
- → Oversized anti-float plate

#### **Materials of Construction**

- $\rightarrow$  Fiberglass basin
- → Galvanized piping
- → Cast Iron valve assembly
- → Aluminum or Steel cover



#### **Booster Systems**

Series 5000 - Vertical Multistage & Horizontal End Suction



#### Application

- → Water Supply
- → Pressure Boosting
- $\rightarrow$  Agriculture
- → Washing/Sprinkling Systems
- → Cooling Circuits
- → Condensate Return

#### Max. Flow

2,100 GPM

#### Max. Head

600 feet

#### **Features & Benefits**

- → Real-time diagnostics and remote monitoring
- → Full system kWh energy reporting
- → Easy to use 7" touchscreen interface
- → Onboard MODbus and optional BACnet and LONworks interface
- → Variable speed control per pump
- → Adjustable low pressure cut-out
- → Balanced run time for all pumps

#### **Technical Data**

- → Certified to NSF/ANSI 372 & 61
- → Temp range:  $4^{\circ}$ F to  $248^{\circ}$ F (-15°C to 120°C)
- → Electrical Connections: 3~208-230/460/575v
- → Rated pressure: 232 PSI or 363 PSI
- → Flange Connection: 300 class ANSI
- → TEFC motors standard

#### **Materials of Construction**

- → All 304 Stainless Steel construction
- → EPDM/FKM Elastomers
- → Mechanical Seal options
- → Tungsten Carbide/EPDM, or optional Viton®/ **FKM Mechanical Seal**

#### **Oil Smart Systems**

Series 8400



#### Application

- → Elevator pits, containment sites, transformer pits
- → Curve shown above represents stocked units

#### Max. Flow

- 2,500 GPM
- Max. Head
- 155 feet

#### **Features & Benefits**

- $\rightarrow$  Submersible pump, oil sensor, and alarm
- package
- → Single seal submersible floor mount pump
- → Piggyback and direct control designs
- → Conductive pump control sensor → Conductive oil alarm sensor

#### **Technical Data**

- $\rightarrow$  1 & 3 phase
- → 115/208-230/460 volt
- $\rightarrow$  1750 and 3500 RPM pumps
- → Simplex and duplex designs

#### **Materials of Construction**

- → Cast Iron pump
- → Type 4 plastic control box
- → SOOW Cables







#### Weil Condensate Return Systems -**Turbine Pumps**

#### Series 4100

Application

system

Max. Flow

Max. Head

35 GPM

90 feet

→ Simplex or duplex

**Features & Benefits** 

pump and control

 $\rightarrow$  Simple pump pull-out design



 $\rightarrow\,$  Cold and hot water condensate recovery

→ Condensate return system includes tank,

→ Close tolerance regenerative turbine pump

#### 140 120 100 1¼' 80 60 40 11 20 0 0 20 40 60 80 100 Q[GPM]

#### Application

H[ft]

160

- → Cold and hot water condensate recovery system
- $\rightarrow$  Simplex or duplex

#### **Features & Benefits**

- → Condensate return system includes tank, pump, & control
- → End suction centrifugal close-coupled pump design
- → Mechanical alternator

#### **Technical Data**

- $\rightarrow$  1 & 3 phase, 50/60 hz
  - → 115/208-230/460/575 volt
  - → 3500 RPM



#### Weil Control Panels – PLC & PLC/VFD

#### Series 8100

#### Application

- $\rightarrow$  Turns pumps on & off via level controls, including transducers or floats
- → Status indicators, fault indicators for alarm conditions, audible alarms
- $\rightarrow$  Controls pumps used in sump and sewage pumping application

#### Features & Benefits

- → Smart control panels to operate from 1-4 pumps
- → PLC technology, transducer capable, failsafe circuits, advanced communications

#### **Technical Data**

- $\rightarrow$  1 & 3 phase, 50/60 hz
- → 115/208-230/460/575 volt
- $\rightarrow$  UL 508 and UL 698 listed

#### Materials of Construction

- → Steel and coated
- → Fiberglass, Stainless Steel

50

#### **Materials of Construction**

 $\rightarrow$  1 & 3 phase, 50/60 hz → 115/208-230/460/575 volt

→ Steel receiver

**Technical Data** 

→ 1750 RPM

- → Cast Iron pumps/bronze option → Stainless Steel float

Weil Pump





#### Weil Control Panels -**Electromechanical**

#### Series 8100

#### Application

- $\rightarrow$  Turns pumps on & off via level controls,
- → Status indicators, fault indicators for alarm conditions, audible alarms

#### **Features & Benefits**

- → Control panels to operate from 1 to 4 pumps
- $\rightarrow$  Controls pumps used in sump and sewage pumping application

#### **Technical Data**

- $\rightarrow$  1 & 3 phase, 50 & 60 hz
- → 115/208-230/460/575 volts
- $\rightarrow$  UL 508 and UL 698 listed

#### **Materials of Construction**

- $\rightarrow$  Steel and coated
- → Fiberglass, Stainless Steel



#### Weil Level Controls, Junction Boxes, and Alarms

Series 8200, 8300

#### Application

 $\rightarrow$  Clear water pits, sewage pits, SS models for corrosive pits

#### **Features & Benefits**

- $\rightarrow$  High-quality sealed housings that ensure trouble-free operation
- → Variable BUNA power cable

#### **Technical Data**

 $\rightarrow$  115 volt typical, DC for ISR applications  $\rightarrow$  Pilot-duty and full HP models

#### **Materials of Construction**

→ Housing: plastic, delrin, ABS, Stainless Steel → Buna power cable and seals

#### **Technical Data**

 $\rightarrow$  Up to 78" OD, 3/8" or  $\frac{1}{2}$ " thick steel

#### **Materials of Construction**

- → Zinc-plated floor plates and flanges, rubber gaskets
- $\rightarrow$  Steel, Zinc dichromate-plated steel, BUNA rubber, Gastight sealant

51

Weil Pump



#### Weil Basin Covers, Floor Plates, Curb **Rings and Frames**

#### Series 8800

#### Application

- → Round basins for vertical or submersible pumping applications
- → Square basins for vertical or submersible pumping applications

#### **Features & Benefits**

 $\rightarrow$  Thick steel cover with flange kits, float plates, and cable plates



A WILO BRAND

For over 140 years, American–Marsh Pumps has provided pumps for the industrial, municipal, agricultural, commercial and fire protection markets. The pump offerings include end suction, process sump, non–clog self–priming, split–case and ANSI process as well as vertical and submersible turbines. The American–Marsh campus, featuring a 250,000–gallon test laboratory, located in Collierville, Tennessee, was acquired by WILO USA LLC in 2019.





#### 300 Series REC, REF, REI

Close & Flex-Coupled/Inline End Suction Pumps



#### Application

- → Agriculture & Irrigation
- $\rightarrow$  Commercial
- $\rightarrow$  Industrial
- $\rightarrow$  Municipal
- $\rightarrow$  Circulation
- $\rightarrow$  Booster
- $\rightarrow$  HVAC

#### Max. Flow

#### 9,000 GPM

#### Max. Head

450 feet

#### **Features & Benefits**

- → Back pull-out design
- $\rightarrow$  Internal plan 1 seal flush
- $\rightarrow$  CL 250 cast flanges drilled to CL 125
- $\rightarrow$  Centerline discharge
- $\rightarrow$  Integral feet on casing
- → Suction & discharge flanges drilled & tapped for gauges
- → Standard T-frame motors on flex-coupled models
- → REC & REI close-coupled utilize standard C-face T-frame motors

#### **Technical Data**

54

Amercican-Marsh Pumps

- $\rightarrow$  Temperature up to 180°F
- $\rightarrow$  REF base mounted, flex-coupled
- $\rightarrow$  Discharge sizes: 1.25"-12"

#### **Materials of Construction**

- → Cast iron
- $\rightarrow$  Stainless steel fitted
- $\rightarrow$  810 Component seal

#### 320 Series SREM, SOSM

#### Vertical Process Sump Pumps



#### Application

- → Drainage→ Process fluid
- → Sump or storm water

#### Max. Flow

9,000 GPM

#### Max. Head

#### 900 feet

#### **Features & Benefits**

**Technical Data** 

→ Cast iron

→ Temperature up to 180°F

→ Discharge sizes: 1.25"-12"

Materials of Construction

→ Optional metallurgies available

→ Stainless steel fitted

- → Enclosed or semi-open impellers
- $\rightarrow\,$  Custom lengths available up to 20 feet

#### 340 Series HD

**Double Suction Split Case Pumps** 



#### Application

- $\rightarrow$  Circulation
- $\rightarrow$  Booster
- $\rightarrow$  HVAC
- $\rightarrow$  Transfer
- $\rightarrow$  Cooling tower
- → Agriculture & Irrigation

#### Max. Flow

#### 16,000 GPM

#### Max. Head

550 feet

#### **Features & Benefits**

- $\rightarrow$  Double suction impellers
- → Heavy-duty construction
- → Replaceable bearings without full disassembly
- → Case case wear rings
- → Internal plan 1 flush

#### **Technical Data**

- $\rightarrow$  Temperature up to 180°F
- $\rightarrow$  Base mounted, flex-coupled
- → Discharge sizes: 2.5"-14"

#### **Materials of Construction**

- → Cast iron
- $\rightarrow$  Bronze fitted
- → Packed or mechanical seal
- → Optional metallurgies available

AMERICAN-MARSH PUMPS





#### 380 Series HH

Two-Stage Horizontal Split Case Pumps



#### Application

- → Boiler feed
- $\rightarrow$  Condensate
- $\rightarrow$  High pressure booster

#### Max. Flow

900 GPM

#### Max. Head

950 feet

#### **Features & Benefits**

- → High head
- → Opposed impellers
- $\rightarrow$  Optional ring–oiled lubrication

#### **Technical Data**

- $\rightarrow$  Temperature up to 250°F
- $\rightarrow$  Base mounted, flex-coupled
- $\rightarrow$  Discharge sizes: 1.5" to 4"

#### **Materials of Construction**

- $\rightarrow$  Cast iron
- $\rightarrow$  Bronze fitted

#### 460 Series OSD

ANSI B73.1 Process Pumps



#### Application

#### → Process

- $\rightarrow$  Petrochemical
- → Pulp & paper
- $\rightarrow$  Steel mills
- → Municipal

#### Max. Flow

#### 7,000 GPM

#### .....

Max. Head

#### 900 feet

#### **Features & Benefits**

- → Reverse-vane
- → Semi-open & low flow impellers
- → Back pull-out
- → Heavy-duty
- → Multiple stuffing box configurations

#### **Technical Data**

- $\rightarrow$  Temperature up to 250°F
- $\rightarrow$  Base mounted, flex-coupled
- $\rightarrow$  Discharge sizes: 1"-8"

#### Materials of Construction

- → Stocked in cast steel & 316 SS, CD4 is available
- $\rightarrow$  Optional metallurgies available

#### **480 Series Vertical Turbine**

Open & Enclosed Lineshaft, Submersible, Axial & Mixed Flow Pumps



#### Application

- → Steel mill
- → Power plant
- → Water well
- $\rightarrow$  Commercial
- $\rightarrow$  Irrigation
- $\rightarrow$  Municipal

#### Max. Flow

#### 30,000 GPM

- Max. Head
- 1.000 feet

#### **Features & Benefits**

- → Modular design enameled bowls through 15" for VT
- → Cast iron, 316 stainless steel fitted for VT
- → Cast iron, bronze fitted for axial & mixed flow pumps
- $\rightarrow\,$  Cast iron or fabricated steel discharge heads
- → Semi-open, enclosed, axial & mixed flow impellers

#### **Technical Data**

- $\rightarrow$  Temperature up to 180°F
- $\rightarrow$  Bowl diameters: 5"-42"

#### **Materials of Construction**

- → Cast iron
- → Bronze or stainless steel fitted
- → Optional metallurgies available

# American-Marsh Pumps





#### 490 Series SXT & SXU

Self-Priming Pumps



#### Application

- $\rightarrow$  Lift station
- → Sewage
- → Storm water
- → Sewer bypass

Max. Flow

6,400 GPM

#### Max. Head

260 feet

#### **Features & Benefits**

- $\rightarrow$  Self-primer
- → Open impeller
- → Replaceable wear plate
- → Back pull-out, clean-outs
- → Belt driven & flex coupled
- → Dual oil reserviors with indicators

#### **Technical Data**

- → Temperature up to 160°F
- → Discharge sizes: 2"-12"

#### **Materials of Construction**

- → Cast iron
- → Optional metallurgies available

#### **500 Series FP-VT Fire**

Vertical Turbine Fire Pumps

FN

APPROVED

**800 Series Mechanical Seals** 



#### Application

- → Industrial
- → Commercial
- → Municipal
- → Mining

#### Features & Benefits

- → Unique design drive bands minimize wear on shaft or sleeve surface
- $\rightarrow$  Precision lapped seal faces
- → Wide variety of seal faces and elastomers available
- $\rightarrow$  Non-clogging, single coil spring
- → Self-aligning capability
- → High-quality stainless steel metal parts

#### **Technical Data**

- $\rightarrow$  Temp. range: -40°F to +400°F
- → 3600 RPM
- → Pressures up to 425 PSI
- $\rightarrow$  Sizes 1" to 4"

#### **Available Face Materials**

- $\rightarrow$  Carbon
- → Silicon-Carbide
- → Tungsten-Carbide

**Technical Data** 

→ Temperature up to 120°F

→ Modular bowl assemblies

→ Packaged with driver & controller

→ 1,500 to 1,800 RPM

#### **Materials of Construction**

- → Cast iron

Amercican–Marsh Pumps

56

- $\rightarrow$  Bronze fitted
  - → Bronze impellers

Max. Flow

Application

→ Fire Protection

4,500 GPM

#### Max. Head

840 feet

 $\rightarrow$  Packed

#### **Features & Benefits**

 $\rightarrow$  UL/FM certification  $\rightarrow$  Cast iron/bronze fitted





Vertical, Horizontal & Submersible





#### ATL, PWS, VFD

**Control Panels** 

#### Application

- $\rightarrow$  Agriculture & Irrigation
- → Commercial/HVAC
- $\rightarrow$  Industrial
- $\rightarrow$  Municipal

#### **Features & Benefits**

- $\rightarrow$  NEMA Type 1
- $\rightarrow$  NEMA Type 3
- $\rightarrow$  NEMA Type 3R

#### → Cooling coils available

**Features & Benefits** 

Application

→ Industrial

 $\rightarrow$  Municipal

→ Fire

→ Agricultural

**Right Angle Gear Drives** 

For 480 Series Vertical Turbines

- $\rightarrow$  Non-reverse clutches
- $\rightarrow$  Rigid castings designed to insure correct alignment
- $\rightarrow$  Gears are case hardened alloy steel, lapped in pairs
- $\rightarrow$  Positive pressure oil distribution systems
- → Bearings exceed AGMA recommendations

#### **Technical Data**

**Materials of Construction** 

 $\rightarrow$  Industry standard

 $\rightarrow$  Gear drives rated from 1,000 HP to over 8,000 HP

#### $\rightarrow$ 1/2 HP to over 1,000 HP

→ 50 Hz & 60 Hz

→ Multiple HP ranges

**Technical Data** 

→ Speeds: 514-3,600 RPM

#### **Materials of Construction**

**Motors** 

Application

 $\rightarrow$  Industrial

→ Municipal

 $\rightarrow$  Fire

→ Agriculture & Irrigation

→ Commercial/HVAC

Features & Benefits

→ WPI, TEFC, ODP

→ Horizontal, vertical & submersible

 $\rightarrow$  Canned style submersibles

#### $\rightarrow$ Industry standard

#### **Materials of Construction**

→ Industry standard

# BEY( THE OB



# wilo



092821

#### WILO USA LLC

+1 262-204-6600 www.wilo-usa.com info.us@wilo.com

#### WILO Canada Inc.

+1 403-276-9456 www.wilo-canada.com info@wilo-canada.com

#### Scot Pump

+1 262-377-7000 www.scotpump.com scot.sales@wilo.com

#### Weil Pump

+1 262-377-1399 www.weilpump.com weil.sales@wilo.com

American-Marsh Pumps, LLC +1 901-860-2300 www.american-marsh.com amp@wilo.com

