

Pioneering for You

wilo

Wilo-Medana CH1-L

Non-self-priming Multistage horizontal centrifugal pumps





Field of application	Cooling circuits, Car wash
Duty chart	
Construction	Non-self-priming Multistage horizontal centrifugal pumps
Application	Pumping of process water and drinkingwater for: irrigation, pressure boosting, industrial applications
Volume flow Q_{max}	24 m ³ /h
Delivery head H_{max}	69 m
Special features	<ul style="list-style-type: none"> → Captive nuts on connections (option) → Cataphoretic-coated lantern → Oblong hole for fixation → Compact design → ACS approval
Technical data	<ul style="list-style-type: none"> → Mains connection: 1~230 V, 50/60 Hz – 3~380/400/460 V, 50/60 Hz → Rated pressure: 10 bar → Fluid temperature: -20 °C to 120 °C → Ambient temperature: -15 °C to 50 °C → Protection class: IP55
Equipment/function	<ul style="list-style-type: none"> → Pump housing and impellers made of stainless steel → AC motor: 3~ > 0.75 AC IE3, 3~ < 0.75 AC IE2 → AC motor: 1~ AC IE1/E2 → Threaded connection

WILO Mather and Platt Pumps Pvt. Ltd.
 1st Floor, "One Elpro Park",
 Elpro Compound, CTS No.4270,
 Chinchwad, Pune – 411033.
 Maharashtra (India)

T +91 20 67347100 / 200
 Service Toll Free: 1800 266 8866

www.wilo.in
sales.in@wilo.com

www.facebook.com/WiloIndia

Tech. matter subject to change without prior notice
 Images are for representation purpose only, actual product may differ.