

## **UL Listed Pumps**

Wilo – Atmos ISO FF





Field of application	Fire fighting
Duty chart	200
Construction	End Suction back pull out type pump mounted on a baseplate.
Application	Motor/Engine driven pumps suitable for : → Hydrant → Sprinkler
Volume flow Q <sub>max</sub>	1000 usgpm
Delivery head H <sub>max</sub>	165 m
Special features	<ul> <li>→ Pump designed in accordance with UL</li> <li>→ NFPA standards with UL certification</li> <li>→ Complete set with UL listed mandatory accessories</li> <li>→ Robust design, with low maintenance.</li> <li>→ Flanges in accordance to – ANSI standards.</li> </ul>
Technical data	<ul> <li>→ Fluid temperature: Upto +105 °C</li> <li>→ Prime mover: Motor/Engine</li> <li>→ Nominal diameters: DN 50 to DN 100</li> <li>→ Operating pressure: 16 bar</li> </ul>
Equipment/function	<ul> <li>→ Optional Features for Engine set :</li> <li>→ Can be supplied with RC/HE cooling options.</li> <li>→ Loose supply - Battery, battery cable</li> <li>→ Auto Engine (ADEP), Residential silencer</li> </ul>

WILO Mather and Platt Pumps Pvt. Ltd. Mumbai-Pune Road, Chinchwad, Pune – 411019. Maharashtra (India)

www.wilo.in sales.in@wilo.com

www.facebook.com/WiloIndia