

Pioneering for You


wilo



Wilo Pumps and Pumping Systems

Wilo-Vertical Turbine Pumps



	Vertical Turbine Pumps	: 87 models
	Series	: CNE /VMF /VMP /RN-V / Atmos TERA-VMF
	Flow Range++	: up to 50000 m3/hr
	Head Range	: up to 450 mtr
	Operating Temperature	: 0°C to 80°C, Higher on request
	Mounting	: Vertical
	Orientation	: Above Floor, Below Floor
	Trust Bearing Lubrication	: Grease , Oil
	Line Shaft Bearing Lubrication	: Self, Forced [external]
	Direction of Rotation	: Clockwise, Counter Clockwise
Bowl Assembly	: Pull out or Non-pull out	
Material of Construction :	Casing : Cast Iron, Stainless Steel, Duplex SS, Cast steel Impeller : Cast Iron, Stainless Steel, Bronze, Cast Steel, Duplex SS	
Application :	<ul style="list-style-type: none"> → Water Supply/Irrigation → Cooling water for power plant → Flood Control/Condensate → Extraction → General Industry/Fire fighting → Sea water/offshore/onshore 	
Volume Flow Q Max :	50000 m3/hr	
Delivery Head Max :	450 mtr	
Special features :	<ul style="list-style-type: none"> → Above floor/below floor → Single/multistage → Caission/canister construction → Tilted pad thrust bearings with cooling arrangement, semi-open impellers → Intermediate bearings lubrications-Pumped medium/oil/external water → Engine driven with right angle gear box 	