

Zubehör - Accessories - Accessoires

Miniprop TR14 ... TR28 + Flumen EXCEL / OPTI TRE20 ... TR28-1
 Rahmen vert. verstellbar - Frame vert. adjustable - Bâti réglable vert.




Heimgartenstraße 1-3 D-95030 Hof/Saale
 Telefon +49 9281 974-0 Fax +49 9281 96528
 www.wilo.com E-Mail: info@wilo.com

Kunde Projekt Angebot - Quotation - Offre
 Customer Project Auftrag - Order - Commande
 Client Projct Nr. - No.:


Führungsrohrlänge Standard L= 6 m
 Guide pipe length L1= L2= L3= m
 Longueur du tube de guidage

Teile - parts - pièces séparées
 montiert - mounted - monté

Schwenkbereich auftragsbezogen prüfen!!!
 Working range - depending on order!!!
 Gamme d'orientation - dépendant de la commande!!!



Flumen TRE20 .. TR28-1
 Miniprop




AVU 50

 KMAT
 6000553



6011006
 A2
 A4

6031441



6010940 Ø10-17
 6010939 Ø17-25




AVU 60

 KMAT
 6000553



6011006
 A2
 A4

6031442



6010940 Ø10-17
 6010939 Ø17-25



TR xx. ___ - ___ /6
 TR xx. ___ - ___ /11
 TR xx. ___ - ___ /13

KMAT 6000232 - TR 14
 KMAT 6000233 - TR 16
 KMAT 6000234 - TR 21
 KMAT 6084656 - TR 20-1
 KMAT 6088723 - TRE 20

KMAT 6000242 - TR 28
 KMAT 6088724 - TR 28-1


AVU 80

 KMAT
 6000553



6010954
 A2
 A4

6031450



6010940 Ø10-17
 6010939 Ø17-25



6011005

A4 = 1.4571 / AISI 316Ti / Z 6 CNDT 17-12

A2 = 1.4301 / AISI 304 / Z 7 CN 18-09

= Befestigungssatz / fixing elements / éléments de fixation