


Pioneering for You

Submersible mixer

Flumen EXCEL-TRE 30.117-6/16



Unit

Power consumption at duty point $P_{1,1}$	1.94 hp
Max. thrust F	74.2 lbf
Thrust to power ratio	38 lbf/hp
Max. weight* m	198.4 lb
Explosion protection ATEX ATEX	optional
Explosion protection FM FM	optional
Protection class motor	IP68

Propeller

Propeller model	3-blade propeller with self-cleaning hub; clogging- and entwining-free
Nominal propeller diameter D_{nom}	11.8 in (*)
Propeller speed n	1167 RPM
Transmission ratio	1.000

Filling quantities and types

Filling sealing chamber	White oil
Fill volume sealing chamber V	0.3 US gal

Motor/electronics

Motor type	TE 17-6/16R (Ex)
Motor design	Submersible motor – surface-cooled
Mains connection	3~460 V, 60 Hz
Rated current I_N	4.00 A
Starting current - direct I_A	39.00 A
Starting current - star-delta I_A	13.00 A
Power consumption $P_{1 max}$	2.8 hp
Rated power P_2	2.4 hp
Speed original n	1167 RPM
Motor efficiency class	IE3
Efficiency η_M	85.8 %
Power factor $\cos \varphi$	0.66
Min. fluid temperature T_{min}	37 °F
Max. fluid temperature T_{max}	104 °F
Max. immersion depth	66 ft
Insulation class	H
Max. switching frequency t	15 rph
min. switching break t	3 min
Starting torque M	59.0 lbf ft
Moment of inertia	0.49 lb ft ²
Motor bearings	1 grooved ball bearing, 1 two-row inclined ball bearing

Materials

Motor housing	ASTM A48, Class No. 35
Static gaskets	FKM Fluoro rubber
Motor shaft	AISI 420
Sealing chamber	AISI 316
Propeller	AISI 316

*maximum weight including accessories