


Pioneering for You

## Submersible mixer EMU TRE 216.49-6/16



### Unit

Power consumption at duty point $P_{1,1}$	1.74 hp
Max. thrust $F$	233.8 lbf
Thrust to power ratio	132 lbf/hp
Max. weight* $m$	449.7 lb
Explosion protection ATEX	optional
Explosion protection FM	optional
Protection class motor	IP68

### Propeller

Propeller model	2-blade propeller with self-cleaning hub; clogging- and entwining-free
Nominal propeller diameter $D_{nom}$	63.0 in (*)
Propeller speed $n$	49 RPM
Transmission ratio	24.056

### Filling quantities and types

Filling prechamber	Gear oil CLP220
Filling volume prechamber $V$	0.3 US gal
Filling gear chamber	Gear oil CLP220
Fill volume gear chamber $V$	0.2 US gal
Filling sealing chamber	White oil
Fill volume sealing chamber $V$	0.3 US gal

### Motor/electronics

Motor type	TE 17-6/16R (Ex)
Motor design	Submersible motor – surface-cooled
Mains connection	3~230 V, 60 Hz
Rated current $I_N$	8.00 A
Starting current – direct $I_A$	78.00 A
Starting current – star-delta $I_A$	26.00 A
Power consumption $P_{1 max}$	2.8 hp
Rated power $P_2$	2.4 hp
Speed original $n$	1167 RPM
Motor efficiency class	IE3
Efficiency $\eta_M$	85.8 %
Power factor $\cos \varphi_{100}$	0.66
Min. fluid temperature $T_{min}$	37 °F
Max. fluid temperature $T_{max}$	104 °F
Max. immersion depth	66 ft
Insulation class	H
Max. switching frequency $t$	15 rph
min. switching break $t$	3 min
Starting torque $M$	59.0 lbf ft
Moment of inertia	0.49 lb ft <sup>2</sup>
Motor bearings	2 grooved ball bearing

### Materials

Motor housing	ASTM A48, Class No. 35
Static gaskets	FKM Fluoro rubber
Motor shaft	AISI 420
Seal, gear/sealing chamber	SiC/SiC, Q1Q1VGG
Gear housing	ASTM A48, Class No. 35
Planetary gear	AISI 5115
Hollow gear	Grade 60
Sun gear	AISI 5115
Output shaft	AISI 329
Seal, gear chamber/prechamber	FKM Fluoro rubber
Sealing chamber	ASTM A48, Class No. 35
Seal bushing	AISI 316Ti
Propeller hub	ASTM A536, Grade 60-40-18
Propeller	VE-GFRP

### Gear

Gear construction type	m 2.0 as per DIN 780-1:1977-05 /P10 (ISO54:1996-12); sun and planetary gears case hardened and sanded, internal gear butt-jointed
Gear bearings	Six needle roller bearing (planetary), two tapered roller bearings (output shaft adjustable type), gearing permanently fixed
Service life $L_{h10}$	100,000 operating hours, ISO 281:2007-02

\*maximum weight including accessories

Subject to change without prior notice.