


Pioneering for You

Submersible mixer EMU TRE 321.37-4/12



Unit

Power consumption at duty point $P_{1,1}$	2.61 hp
Max. thrust F	427.1 lbf
Thrust to power ratio	161 lbf/hp
Max. weight* m	485.0 lb
Explosion protection ATEX ATEX	optional
Explosion protection FM FM	optional
Protection class motor	IP68

Propeller

Propeller model	3-blade propeller with self-cleaning hub; clogging- and entwining-free
Nominal propeller diameter D_{nom}	82.7 in (*)
Propeller speed n	37 RPM
Transmission ratio	46.500

Filling quantities and types

Filling prechamber	Gear oil CLP220
Filling volume prechamber V	0.3 US gal
Filling gear chamber	Gear oil CLP220
Fill volume gear chamber V	0.2 US gal
Filling sealing chamber	White oil
Fill volume sealing chamber V	0.3 US gal

Motor/electronics

Motor type	TE 17-4/12R (Ex)
Motor design	Submersible motor – surface-cooled
Mains connection	3~230 V, 60 Hz
Rated current I_N	10.80 A
Starting current – direct I_A	82.00 A
Power consumption $P_{1 max}$	4.7 hp
Rated power P_2	4.0 hp
Speed original n	1746 RPM
Motor efficiency class	IE3
Efficiency η_M	86.7 %
Power factor $\cos \varphi$	0.81
Min. fluid temperature T_{min}	37 °F
Max. fluid temperature T_{max}	104 °F
Max. immersion depth	66 ft
Insulation class	H
Max. switching frequency t	15 rph
min. switching break t	3 min
Starting torque M	49.4 lbf ft
Moment of inertia	0.26 lb ft ²
Motor bearings	2 grooved ball bearing

Materials

Motor housing	ASTM A48, Class No. 35
Static gaskets	FKM Fluoro rubber
Motor shaft	AISI 420
Seal, gear/sealing chamber	SiC/SiC, Q1Q1VGG
Gear housing	ASTM A48, Class No. 35
Planetary gear	AISI 5115
Hollow gear	Grade 60
Sun gear	AISI 5115
Output shaft	AISI 329
Seal, gear chamber/prechamber	FKM Fluoro rubber
Sealing chamber	ASTM A48, Class No. 35
Seal bushing	AISI 316Ti
Propeller hub	60-40-15
Propeller	VE-GFRP

Gear

Gear construction type	m 2.0 as per DIN 780-1:1977-05 /P10 (ISO54:1996-12); sun and planetary gears case hardened and sanded, internal gear butt-jointed
Gear bearings	Six needle roller bearing (planetary), two tapered roller bearings (output shaft adjustable type), gearing permanently fixed
Service life L_{h10}	100,000 operating hours, ISO 281:2007-02

*maximum weight including accessories