

2021 Product Brochure - 60 Hz

Wilo-NL-HE

High-Efficiency Base Mount End Suction Pumps



High-Efficiency Base Mount End Suction Pumps

Wilo-NL-HE



Features & Benefits

- → VFD Ready
- → Stainless steel impeller
- → High-Efficiency
- → Improved Hydraulic design
- → Energy Savings
- → Cataphoretic coating of all cast iron components
- → High corrosion resistance
- → Long service life
- → Easy maintenance
- → C-channel construction welded base

Technical Data

- → Temp range -4 °F to 284 °F
- → ANSI Class 125
- → Maximum operating pressure of 232 PSI
- → Main Connection 3~[208–230/460V, 575V] 60Hz
- → EN 1.4408 (Equivalent: AISI 316) Stainless Steel Impellers
- → DIN 1.4021 (Equivalent: 420) Stainless Steel Pump Shaft
- → Antimony Impregnated Carbon/Silicon Carbide/EPDM (E1) Stainless Steel Spring & Body mechanical seal
- → NEMA Premium Efficient Motors

Applications

- → Heating and Cooling Systems
- → Air Conditioning
- → Municipal Water Supply
- → Pressure Boosting
- → Raw Water Intake
- → Irrigation/Agriculture
- → Industrial Process

Max Head: 475 feet Max. Flow: 3,000 gpm

