

Wilo Booster Series Take-Off Sheet
Packaged Booster Systems



Submit orders to: orders.us@wilo.com

Quote #	PO #	Sales Order #

Booster System Data	Select Option
Series:	<input type="checkbox"/> Co-Helix <input type="checkbox"/> SiBooster <input type="checkbox"/> WiBooster <input type="checkbox"/> Other
<input type="checkbox"/> Simplex / <input type="checkbox"/> Duplex / <input type="checkbox"/> Triplex / <input type="checkbox"/> Quadplex	
Model Number:	
Article Number:	
Construction: <input type="checkbox"/> Standard or Custom <input type="checkbox"/>	
Power Supply Voltage: <input type="checkbox"/> 208-230V / <input type="checkbox"/> 460V / <input type="checkbox"/> 575V	
Phase: <input type="checkbox"/> 1 or <input type="checkbox"/> 3 <input type="checkbox"/>	
System Flow (GPM):	
Per Pump Flow (GPM):	
Inlet Pressure (PSIG):	
Boost Pressure (PSIG):	
Discharge Pressure (PSIG):	
Discharge Pressure = Suction Pressure + Boost Pressure	
Standby Pump: <input type="checkbox"/> Y / <input type="checkbox"/> N <input type="checkbox"/>	
% Flow (GPM) per pump:	
Installation Elevation (Ft):	
Fluid Temp. (°F):	
Ambient Temp. (°F):	
Motor Type (Select One):	
<input type="checkbox"/> TEFC (STD - Co-Helix / SiBooster) <input type="checkbox"/> ODP (STD - WiBooster) <input type="checkbox"/> TEFC (Optional - WiBooster)	
Pump Seals & Elastomer:	
<input type="checkbox"/> EPDM-Carb / Sil (STD - WiBooster) <input type="checkbox"/> Other (Please Specify below)	
Optional Tank Info: <input type="checkbox"/> ASME / Non ASME <input type="checkbox"/>	
Gallons:	
PSI:	
Article No:	

Optional Features	Select Option
<input type="checkbox"/> Pump Run Light	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> (1, 2, 3, 4)
<input type="checkbox"/> Pump Fault Light	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> (1, 2, 3, 4)
<input type="checkbox"/> Exhaust Fan Kit - Type 3R in lieu of 12	
<input type="checkbox"/> Surge Protection (3 Phase)	208-230V 460V 575V
<input type="checkbox"/> Stainless Enclosure - 304SS Enclosure in lieu of Steel	
<input type="checkbox"/> 304SS Baseplate - In lieu of Nickel Plated Steel	
<input type="checkbox"/> Panel Protection Cover (clear)	
<input type="checkbox"/> Temperature Probe - Includes probe and wiring to panel	
<input type="checkbox"/> Thermal Purge Valve (TPV)*	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> (1, 2, 3, 4)
<input type="checkbox"/> Thermal Purge Valve (TPV) Kit - with tube fitting*	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> (1, 2, 3, 4)
<input type="checkbox"/> Dome Light	Green (Run) <input type="checkbox"/> Red (Fault) <input type="checkbox"/> Both <input type="checkbox"/>
<input type="checkbox"/> Pressure Regulating Valve (PRV) - 1 per pump	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> (1, 2, 3, 4)
<input type="checkbox"/> Electrical Bypass Circuit & Switch	
<input type="checkbox"/> BACnet Gateway Communications	
<input type="checkbox"/> Sun shade for HMI (lockable)	
<input type="checkbox"/> Shaft Grounding Ring	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> (1, 2, 3, 4)
<input type="checkbox"/> Weather Hood - 304SS	
<input type="checkbox"/>	
<input type="checkbox"/>	

***Co-Helix, SiBooster - 1 per system on suction manifold**
WiBooster - 1 per pump on pump case

Manifold entry/exit system connections (Facing Panel HMI):

Suction: Left Right Other
Discharge: Left Right Other

Quoted Lead Time: _____

Date: _____

Submitted By: _____

Comments: _____
