



Certificate number: 2012716

Date issued 8th December 2020

Date expired 7th December 2025 Orignal/Amendment Original

Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 - Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004 Reference Standards: Regulators Specification Model Designations: see Appendix

Factor: WILO.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification, which is managed in accordance with ISO/IEC 17065.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory Kiwa Watertec

(A Trading Division of Kiwa Ltd) 26A Rassau Industrial Estate Ebbw Vale Gwent NP23 5SD United Kingdom T +44 (0)1495 308185 uk.water@kiwa.com www.kiwa.co.uk

Kiwa Watertec

Certificate issued to: WILO 80 Boulevard de l'Industrie 53005 LAVAL France





Appendix to Certificate 2012716

The following products are covered by this certificate -

| PRODUCT DESCRIPTION: |
|---|
| Range of inline circulating pumps with bronze bodies, plastic impeller and EPDM rubber seals. |
| ATS3 – Without Production Surveillance. |
| MODEL(S): |
| STAR-Z 20/1 – inlet 1"; |
| STAR-Z 25/2 – 1 1/2"; |
| STAR-Z 20/2-3(15-130) – 1"; |
| STAR-Z 20/4-3(150) – 1 ¼"; |
| STAR-Z 20/5-3(150) – 1 ¼"; |
| STAR-Z 25/6 – 1 1/2"; |
| STAR-Z 20/7-3(150) – 1 ¼"; |
| STAR-ZD 25/6 – 1 1/2". |
| SIZE: |
| See model. |
| SCOPE: |
| Supplier recommended maximum working pressure 10 Bar & maximum operating temperature 100°C. |
| Hygienic purposes: Non-metallic materials suitable for continuous use up to 85°C. |
| Above ground use only. |
| MATERIALS: |
| Non-Metallic materials assessed (BS6920) to point of discharge. |
| BACKFLOW PROTECTION NOTES: |
| N/A. |
| MARKING: |
| WILO, PN, Serial No, Date of Manufacture (YYWW) and other technical information. |
| ADDITIONAL NOTES: |
| Opacity. |
| All water contact & exposed components satisfy opacity requirements. |
| |

Extra Notes: