



Certificate number: 2304771 (3)

Issued 03/04/2024

Expires 02/05/2028

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Wilo SE.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:

Wilo SE.
Wilopark 1
44263 Dortmund
Allemagne
Germany



KUKreg4

Product Certificate

Appendix to Certificate number: 2304771

The following products belong to this certificate

| |
|--|
| <p>PRODUCT DESCRIPTION Range of pumps with stainless steel casings for wholesome water use. ATS3 – Without Production Surveillance.</p> |
| <p>MODEL(S) Yonos PICO-Z 15/0,5-4 130 Stratos PICO-Z 20/0,5-4 Yonos PICO-Z 15/0,5-4 140 Stratos PICO-Z 20/0,5-6 Yonos PICO-Z 20/0,5-4 150 Stratos PICO-Z 20/0,5-8 Yonos PICO-Z 20/0,5-6 150 Stratos PICO-Z 25/0,5-4 Yonos PICO-Z 20/0,5-6 158 Stratos PICO-Z 25/0,5-6 Yonos PICO-Z 20/0,5-8 150 Stratos PICO-Z 25/0,5-8 Yonos PICO-Z 25/0,5-4 180 Stratos PICO-Z 30/0,5-4 Yonos PICO-Z 25/0,5-6 130 Stratos PICO-Z 30/0,5-6 Yonos PICO-Z 25/0,5-6 180 Stratos PICO-Z 30/0,5-8 Model added April 2024: Yonos PICO-Z 25/0,5-8 180</p> |
| <p>SIZE: See model.</p> |
| <p>SCOPE: Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature 65°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 65°C.</p> |
| <p>MARKING Wilo, PN, serial number and other technical information on control box.</p> |
| <p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p> |
| <p>BACKFLOW PROTECTION NOTES N/A.</p> |
| <p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p> <p>Notification should be given in writing of the proposed installation of this fitting to the local Water Supplier prior to its installation. The fitting shall not be installed until consent is given by the Water Supplier in line with Regulation 5 of the Water Supply (Water Fittings) Regulations 1999 or the Water Supply (Water Fittings) Regulations (Northern Ireland) 2009, or Byelaw 5 of the Water Supply (Water Fittings) (Scotland) Byelaws 2014.</p> |

Extra Notes