

# Directory Search Results

---

#1904004

Approved Product

'TOP-Z' range of circulating pumps with stainless-steel (TOP-Z 20/4 & TOP-Z 25/6 models) or gunmetal (RG models) bodies, incorporating EPDM rubber 'O'-rings and PPO impellers. Maximum working pressure 16.0 bar. Maximum operating temperature 80°C.

**Section:** 1610 Pumps (?section=1610)

**Section Subtitle:** Wholesome water use.

**WRAS Approval Number:** 1904004

**Expiry date:** 30/04/2024

**Size:** See model.

**Marking:** WILO, model and PN on data plate. Flow arrow on body.

**Installation Requirements:** R001 (/approvals/testing-requirements/installation\_requirements/irn\_r001)R415 (/approvals/testing-requirements/installation\_requirements/irn\_r415)

**Model:** TOP-Z 20/4 - 1¼" BSP (M) x 1¼" BSP (M).  
TOP-Z 25/6 - 1½" BSP (M) x 1½" BSP (M).  
TOP-Z 30/7 (RG) (open cartridge) - 2" BSP (M) x 2" x 2" BSP (M).  
TOP-Z 25/10 (RG) - 1½" BSP (M) x 1½" BSP (M).  
TOP-Z 30/10 (RG) - 2" BSP (M) x 2" BSP (M).  
TOP-Z 40/7 (RG) - DN40 (flanged) x DN40 (flanged).  
TOP-Z 50/7 (RG) - DN50 (flanged) x DN50 (flanged).  
TOP-Z 65/10 (RG) - DN65 (flanged) x DN65 (flanged).  
TOP-Z 80/10 (RG) - DN80 (flanged) x DN80 (flanged).

**Factor:** Wilo SE.

[View All Listings by this Company \(?company=17990\)](#)