

Life Cycle Assessment Declaration (preliminary calculation)

Wilo-Rexa UNI

Product Info

Owner of the declaration: WILO SE

Declaration No.: Wilo—2024 No. 17.1

lssue date: 26.06.24

Declared product range: Wilo-Rexa UNI

Reference type: Wilo-Rexa UNI-V06A/T015-540/O
Application: Wastewater collection and transport

	CO ₂ -Emissions*:	8,495 kg			
00	Raw materials	162 kg		Raw materials	1,91 %
E	Supply	4 kg		Supply	0,04 %
	Manufacturing	79 kg		Manufacturing	0,93 %
				Distribution	0,00 %
	Distribution	0,3 kg		Use**	97,00 %
PS	Use** \ \ \ \ \ \	8.240 kg		End-of-life	0,12 %

Product Characteristics

End-of-life

→ Efficient product design with components for lowest possible weight

10 kg

- Operational reliability thanks to optimised hydraulics and reduces
 the amount unplanned maintenance intervention work
- Long service life thanks to corrosion-resistant hydraulics in technopolymer and stainless steel motor housing



Owner of the declaration: WILO SE | Wilopark 1 44263 Dortmund | Germany Product Care & Life Cycle Management



Dortmund, 26.06.24

Bjoern Sparbrod Group Vice President,

Group Product & Product Information Management

i.V. Claudía Brasse Group Director, Group Quality, Sustainability Management

ix C. Brasse

The Wilo sustainability strategy implies using (scarce) resources responsibly and with foresight today so that they will still be available tomorrow in sufficient quantities and distributed fairly around the world. At Wilo, one resource is particularly close to our hearts: water. As one of the world's leading premium suppliers of pumps and pump systems for building services, water management and industry, we move this vital element around every day – as intelligently, efficiently and climate-friendly as possible. Resource-conscious thinking and sustainable action are our core competencies and an essential part of our corporate culture.

^{*} extrapolation values based on previous studies

[†] Calculation based on the following assumptions: 1500 hours/year, 10 years, average emission factor EU327 gCO₂/kWh