

Wilo SE. Approvals

#1904007

Approved Product

'Stratos-Z,' 'Stratos PARA Z' and 'Yonos MAXO-Z' ranges of circulating pumps with brass bodies, incorporating EPDM rubber 'O'-rings and either PPO or PPS impellers. Maximum working pressure 16.0 bar. Maximum operating temperature 80°C.

Section: 1610 Pumps (?section=1610)

Section Subtitle: Wholesome water use.

WRAS Approval Number: 1904007

Expiry date: 30/04/2024

Size: See Model

Marking: Company name 'WILO' and model on adhesive label on motor housing. Flow arrow on body.

Installation Requirements: R001 (/approvals/testing-requirements/installation_requirements/irn_r001)

Model: Stratos-Z 25/1-8 RG - 1½" BSP (M) x 1½" BSP (M).

Stratos-Z 30/1-8 RG - 2" BSP (M) x 2" BSP (M).

Stratos-Z 30/1-12 RG - 2" BSP (M) x 2" BSP (M).

Stratos-Z 40/1-8 RG - DN40 x DN40 flanged.

Stratos-Z 40/1-12 RG - DN40 x DN40 flanged.

Stratos-Z 50/1-9 RG - DN50 x DN50 flanged.

Stratos-Z 65/1-12 RG - DN65 x DN65 flanged.

Stratos PARA Z 25/1-8 RG - 1½" BSP (M) x 1½" BSP (M).

Stratos PARA Z 25/1-11 RG - 1½" BSP (M) x 1½" BSP (M).

Stratos PARA Z 25/1-12 RG - 1½" BSP (M) x 1½" BSP (M).

Stratos PARA Z 30/1-8 RG - 2" BSP (M) x 2" BSP (M).

Stratos PARA Z 30/1-11 RG - 2" BSP (M) x 2" BSP (M).

Stratos PARA Z 30/1-12 RG - 2" BSP (M) x 2" BSP (M).

Yonos MAXO-Z 25/0.5-7 RG - 1½" BSP (M) x 1½" BSP (M).

Yonos MAXO-Z 25/0.5-10 RG - 1½" BSP (M) x 1½" BSP (M).

Yonos MAXO-Z 30/0.5-7 RG - 2" BSP (M) x 2" BSP (M).

Yonos MAXO-Z 30/0.5-12 RG - 2" BSP (M) x 2" BSP (M).

Yonos MAXO-Z 40/0.5-8 RG - DN40 x DN40 flanged.

Yonos MAXO-Z 40/0.5-12 RG - DN40 x DN40 flanged.

Yonos MAXO-Z 50/0.5-8 RG - DN50 x DN50 flanged.

Yonos MAXO-Z 65/0.5-12 RG - DN65 x DN65 flanged.

Factor: Wilo SE.

[View All Listings by this Company](#) (?company=17990)