


Pioneering for You

wilo

Vertical mixer

Wilo-Vardo WEEDLESS VM.F6-1/215.16-75
RM87 DRU90S4/C



Drive unit

Drive design	Helical gear motor with corrosion protection OS3/C4
Motor designation	RM87 DRU90S4/C
Mains connection (delta, star)	3~230 V, 3~400 V, 50 Hz
Rated current, direct delta I_N	3.15 A
Rated current, direct star I_N	1.81 A
Power consumption $P_{1\ max}$	0.88 kW
Rated power P_2	0.75 kW
Speed original n	1470 1/min
Motor efficiency class	IE4
Motor efficiency 50	82.3 %
Motor efficiency 75	85.1 %
Motor efficiency 100	85.7 %
Power factor $\cos \varphi_{100}$	0.69
Min. ambient temperature T_{min}	-20 °C
Max. ambient temperature T_{max}	40 °C
Insulation class	F
Protection class motor	IP55
Max. switching frequency t	15 rph
min. switching break t	3 min
Nominal torque M	455 Nm
Explosion protection ATEX	no
Explosion protection FM	no
Motor protection (optional)	Bimetal, PTC
Motor housing	Aluminium
Gear housing	5.1300, EN-GJL-200

Filling quantities and types

Filling gear	Gear oil E 460 (Organic)
Gear fill quantity V	6.8 l

Unit

Power consumption at 40° $P_{1.1}$	0.11 kW
Max. thrust at 40° F	130 N
Thrust to power ratio at 40°	1182 N/kW
Min. fluid temperature T_{min}	3 °C
Max. fluid temperature T_{max}	40 °C
Max. weight m	360 kg

Propeller

Propeller model	2-blade propeller made of solid material
Nominal propeller diameter D_{nom}	1500 mm
Direction of thrust	up/down
Propeller speed n	16 1/min
Transmission ratio	93.380
Propeller hub	PUR Polyurethane
Propeller	PUR Polyurethane

Mixer shaft

Min. length of mixer shaft l	2.0 m
Max. length of mixer shaft l	3.5 m
Mixer shaft	1.4571, X6CrNiMoTi17-12-2

Motor plate

Number of fastening holes	4
Motor plate	1.4571, X6CrNiMoTi17-12-2